

3M™ Digital Projector S55i and X55i



- **Take your presentation to a new level with our sophisticated new design!**
- **Relax. Backed by 3M's quality, reliability and 24/7 technical support.**
- **Versatile - use on the road, in the office, or at home.**
- **Incredible brightness and vibrant color!**

CONNECTIONS

COMPUTER

- RGB (2 inputs, 1 output**)
- USB Mouse Emulation
- Computer Audio (1 input***, 1 output*)
- Serial Control

**RGB Input 2 and Monitor Output share the same connector.

***RGB Input 1 and Input 2 share the Computer Audio Input.


VIDEO

- Composite Video
 - S-Video
 - Component Video
 - Video Audio (1 input, 1 output*)
- *Audio Output is shared with Computer and Video Inputs.

BASIC SPECS

S55i: 2000 lumens X55i: 2000 lumens
SVGA (800 x 600) XGA (1024 x 768)

- 6.4 lbs./2.9 kg
- Vertical Digital Keystone
- HDTV ready



1-800-328-1371
www.3m.com/meetings

3M Innovation

3M™ Digital Projector S55i and X55i



Optical

- Brightness: S55i: 2000 lumens X55i: 2000 lumens
- Imager Set: 0.6", P-Si TFT Panel
- Resolution (native): S55i: SVGA (800 x 600)
X55i: XGA (1024 x 768)
- Resolution (max): UXGA (1600 x 1200)
- Aspect Ratio: 4:3 native, 16:9
- Colors: 16.7 million
- Screen Size (range): 30-301 inches
- Zoom/Focus: manual
- Zoom Ratio: 1:2:1
- Projection Lens: F1.7-1.9, (f = 18.9-22.6 mm)
- Optional Lens: NO
- Contrast Ratio: 400:1
- Lamp: Normal Mode (Whisper Mode): 180 Watt (144 Watt)
- Lamp Life: 2000 hours

Electrical

- Video compatibility: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- SDTV/HDTV 525i (480i), 525p (480p), 625i (576i) / 750p@60Hz, 1125i (1080i@60 Hz)
- Keystone Correction: +/- 15 degrees
- Audio: 1 x 1 Watt
- Startup Screen: Customizable
- Noise Level: Normal (Whisper) 38 dB (33dB)
- Feature Set:
- Horizontal Scan: 31.5 - 106kHz
- Vertical Scan: 56 - 120Hz
- Power Consumption: 290 Watt
- Power Supply: 100 - 120V/220 - 240V, 50/60Hz
- Regulatory Approvals: UL, cUL, FCC part 15 Class B, CE, EN60950
- Operating Temperature: 5 - 35°C
- Storage Temperature: -20 - 60°C

Size

- Dimensions (Wx hxd): 306 x 83 x 249 mm, 12.0 x 3.3 x 9.8 inch
- Weight: 6.4 lbs. (2.9kg)

Warranties

- Projector: 3 year
- Ultra Value Warranty: Available
- Lamp: Replaced before 180 hours or 90 day; Discounted Price for 1 Year

Accessories

- Remote Control (without laser)
- Soft side case
- Power Cords (US, UK, Europe)
- VGA Cable
- RGA Component Cable
- RCA Component Cable
- USB Cable

Optional Accessories

- Lamp (LK55i) 78-6969-9861-2
- Ceiling Mount 78-6969-9860-4
- Soft Carry Case (CC/01/40/50) 78-6969-9715-0
- ATA Rolling Hard Shipping Case (HSC10/40/50) 78-6969-9717-6
- Soft Rolling Luggage Case (SSC10/40/50) 78-6969-9716-8

Projection Distance Chart
3M S55i

Screen Size inches (m)	Min m (inches)	Max m (inches)
30 (0.8)	0.9 (36)	1.1 (43)
40 (1.0)	1.2 (48)	1.5 (57)
50 (1.3)	1.5 (60)	1.8 (72)
60 (1.5)	1.8 (72)	2.2 (87)
70 (1.8)	2.1 (84)	2.6 (101)
80 (2.0)	2.4 (96)	2.9 (116)
90 (2.3)	2.8 (109)	3.3 (130)
100 (2.5)	3.1 (121)	3.7 (145)
120 (3.0)	3.7 (145)	4.4 (174)
150 (3.8)	4.6 (182)	5.5 (218)
200 (5.1)	6.2 (242)	7.2 (291)
250 (6.4)	7.7 (303)	9.3 (364)
300 (7.6)	9.2 (364)	11.1 (437)

Projection Distance Chart
3M X55i

Screen Size inches (m)	Min m (inches)	Max m (inches)
30 (0.8)	0.9 (36)	1.1 (43)
40 (1.0)	1.2 (48)	1.5 (58)
50 (1.3)	1.5 (60)	1.8 (73)
60 (1.5)	1.8 (73)	2.2 (87)
70 (1.8)	2.2 (85)	2.6 (102)
80 (2.0)	2.5 (97)	3.0 (117)
90 (2.3)	2.8 (109)	3.3 (132)
100 (2.5)	3.1 (122)	3.7 (146)
120 (3.0)	3.7 (146)	4.5 (176)
150 (3.8)	4.6 (183)	5.6 (220)
200 (5.1)	6.2 (244)	7.5 (294)
250 (6.4)	7.8 (306)	9.3 (367)
300 (7.6)	9.3 (367)	11.2 (441)

www.3m.com/meetings

Important Notice

All statements, technical information, and recommendations related to 3M's products are on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publication, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of three years from the date of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

3M Visual Systems

Building A 147-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Mexico, S. A. de C. V.

Apartado Postal 14-139
Mexico, D. F. 07070
Mexico

3M Canada

P. O. Box 5757
London, Ontario,
Canada
N6A 4T1

©3M 2005 111505
78-6970-8619-3

3M Innovation