

Armadillo



BRIGHTNESS

2600 ANSI lumens

RESOLUTION

800 x 600 true SVGA
1280 x 1084 SXGA
compressed

DISPLAY TYPE

3 - 0.7 in TFT
Polysilicon LCDs

CONTRAST RATIO

500 : 1

WEIGHT

6 lbs / 2.7 kg

DIMENSIONS

12.2 x 3.8 x 10.6 in
310 x 96 x 270 mm

LAMP

180 watts, NSH

LAMPLIFE

2000 hours

DIAGONAL IMAGE SIZE

40 - 300 in

PROJECTION LENS

manual zoom 1:1.2 ratio,
F / 1.75 - 2.1 F=26.7 - 32mm

TROW DISTANCE

4.75 - 37.4 ft
1.45 - 11.29 mm

INPUTS

2 - 15 pin VGA
1 - Composite
1 - S Video
1 - Component
1 - Mini jack audio

OUTPUTS

1 - RGB
1 - USB mouse
1 - RS 232



*A projector sits inside an airtight cabinet that is built to resist dust, smoke and water vapor. The cabinet case is made of iron material and therefore can endure force from outside.
patent pending*

Input Panel



Automatic set-up and direct key access for major functions make the Armadillo easy to use.

SPECIAL FEATURES:

It can be used in a high temperature environment since the compressor keeps providing cool air to the projector. The projector's life time can be extended due to the constant air temperature and free of dust and smoke in the cabinet.

AUDIO

1 X 2 watt speakers

KEystone

+ / - 30° vertical

POWER SUPPLY

100-240V, 50/60Hz
UL Certified

VIDEO

NTSC, PAL, SECAM,
1080i, 720p, 480p

DECIBEL RATING

33dB / 30dB eco

FCC CERTIFICATION

Class B

SHIPS WITH:

Remote control	Audio cable - RCA (L/R)
USB mouse cable	S-Video
Composite AV cable	Soft carry case
Power cord	User manual
VGA cable	

WARRANTY:

Two year parts and labor (120-day/500 hour lamp guarantee)

BOXLIGHT®
Presenting a Better Way

19302 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct - 800.762.5757
International - 360.779.7901
Partners - 866.688.3636