

# Pro4500DP

## FEATURES:

- 5000 ANSI lumens
- Built in RJ-45 Lan connectivity
- Intelligent dual lamp system
- Power lens shift
- (2) 3 watt stereo speakers
- Six lens options

## SHIPS WITH:

- Remote control
- User manual
- Power cord
- RGB cable
- M1-D cable
- Audio/Video cable
- Lens cap

## WARRANTY:

- Three year parts and labor
- 90-day lamp guarantee

## OPTIONAL ACCESSORIES:

- Mac adapter
- Ceiling mount
- ATA case
- Kensington lock
- Wide fixed lens
- Short throw lens
- Ultra long throw lens
- Long zoom lens
- Med / long lens
- Replacement lamp

Automatic set-up and direct key access for major functions make the Pro4500DP easy to use.



## BRIGHTNESS

5000 ANSI lumens

## RESOLUTION

1024 x 768 true XGA  
Compressed 1280 x 1024 SXGA

## DISPLAY TYPE

TI DMD 0.7", 12°, DDR  
DLP with DDP 2000 ASIC controller

## CONTRAST RATIO

800:1

## LAMP

2 x 250 watts

## LAMP LIFE

2000 hours

## COMPATIBILITY

SXGA, XGA, SVGA, VGA, Mac



With dual 250 watt high brightness lamps, the Pro4500DP achieves 5000 ANSI lumens with superb contrast and uniformity. It delivers bright clear images in large highly lit rooms.

## PROJECTION LENS

Power zoom and focus  
1.22:1 zoom ratio

## INPUTS

(1) DVI-D, (1) BNCx5, (1) DB-15, (1) Composite video, (1) S-Video, (1) Component (through BNC to RCAx3 adapter), (1) HDMI digital video, (1) RCA audio (L/R), (3) Audio mini jack, (1) RS232, (1) RJ-45

## OUTPUTS

(1) DB-15 (loop through), (1) Audio mini jack out  
(1) USB mouse

## THROW DISTANCE

3.2 - 32.8 ft  
1.0 - 10 m

## KEYSTONE

Vertical and horizontal adjustment of + / - 40°

## VIDEO

NTSC, NTSC4.43, PAL (B/G/H/I/M/N 60), SECAM

## AUDIO

Dual 3-watt stereo speakers

## POWER SUPPLY / CONSUMPTION

100 - 240V, 50 - 60 Hz auto change, 650 watts

## DECIBEL RATING

38dB

## DIMENSIONS

16.14 x 7.08 x 18.54" in  
41 x 18 x 47 cm

## WEIGHT

33 lbs / 14.9kg



www.boxlight.com/procolor  
866.688.3636  
19302 Powder Hill Place  
Poulsbo, WA. 98370