



2300 Lumens



At 3.96 pounds the Casio Super Slim™ projector won't weigh you down.

Casio Super Slim projectors take the hassle out of travel so you can be the ultimate road warrior. At just under four pounds, it's lighter than most laptops so it won't weigh you down. At 1.7" thick its thin profile will make packing for travel a breeze...forget the extra bags, just stow it away in your briefcase.



Traveling with the Casio Super Slim couldn't be easier - whether you use your laptop, or the PC free option.

**2X
Power Zoom**

Short Throw Power Zoom and Focus Lens

Whether you are in a small office or a large boardroom the Super Slim's 2X power zoom lens gives you the flexibility to easily position the projector. Large screen projection is possible in any room and the short throw lens (1.4-2.8 throw ratio) can project an image from as close as 3' and up to 28' back. Image adjustment can be easily made from the remote control or an RS-232 control system.

RS-232 Control Connectivity

No more compromising. Casio's Super Slim projectors incorporate RS-232C control for easy system integration. The Super Slim's low profile and elegant design looks great in any Boardroom Conference or Classroom. Compatible with industry standard control systems (AMX, Crestron and Extron) the Super Slim projectors boast an available command set which includes Power On/Off, Input select and Lens Zoom and Focus.



Ceiling mount commercially available (sold separately).



RS-232 cable optional and sold separately.

Key Features:

- XGA (1024 x 768) Native Resolution, UXGA max
- DTV/HDTV - 480i/480P/720P/1080i/1080p
- DLP Display Technology from Texas Instruments
- 2X Power Zoom and Focus Short Throw lens

Includes:

- Built-in 1watt Speaker
- Remote Control
- Storage Case for Projector and Cables
- Cables for PC, Power and Video
- 3 years Parts and Labor Warranty (180 day warranty on lamp)



| BASIC SPECIFICATIONS | | |
|---------------------------------|----------------------------|--|
| * Brightness (lumens) | Eco-Mode: OFF | 2300 lumens |
| * Contrast ratio | Telephoto mode | 1800:1 |
| Lamp | High-pressure mercury lamp | 210W |
| Estimated Lamp life | | Up to 2,000 hours |
| Keystone correction | Auto | +30° |
| | Manual | ±30° |
| Projection lens | | 2X Power Zoom and Focus |
| Projection screen size | | 15 ~ 300-inch |
| Projection range | 60-inch screen | 5.57 feet to 11.15 feet |
| | 100-inch screen | 9.18 feet to 18.37 feet |
| | Minimum | 2.75 feet |
| | Projection ratio | 1.4-2.8:1 |
| Projection system | | DLP® system |
| Display element | Device Type | 0.55-inch DLP® chip |
| | Native Resolution | XGA (1024 x 768) 786,432 pixels |
| Computer Signal Compatibility | Maximum | UXGA (1600 x 1200) (Compressed) |
| | Resolutions | SVGA, XGA, WXGA, SXGA, SXGA+, WXGA+, WSXGA+, UXGA |
| Video Signal Compatibility | Hor./Vert. Frequency | fH 31.5-91.1 kHz / fV 56-85 Hz |
| | Video Systems | NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM |
| | DTV/HDTV | 480i/480P/576i/576P/720P/1080i/1080p |
| Color reproduction | | Full color (16.77 million colors) |
| Power source | | AC100~240V, 50/60Hz |
| Power consumption | Operating | 270W (Eco-Mode:220W) |
| Usage environment | Operating temperature | 41-95° F (5~35°C) |
| | Operating humidity | 20~80% (non-condensation) |
| | High Altitude Mode | Yes (for operation 5000 ft to 10000 ft above sea level) |
| INTERFACE TERMINALS | | |
| RGB/Component Video Input | | mini D-Sub 15 pin x 1 Also use as YcbCr/YPbPr input |
| Audio | Input | 3.5mm mini-jack |
| | Output | 1 W speaker 3.5mm mini-jack (shared with Audio Input) |
| Video | Input terminals | Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr |
| Control | Terminal | RS-232C Adapter cable (YK-5) required and sold separately |
| | System Compatibility | AMX, Crestron, Extron and SP Controls |
| OTHERS | | |
| Dimensions | | 10.63" x 7.83" x 1.69" Including projections (1.26" at thinnest point) |
| Weight | | 3.96 lbs. |
| Security compatibility | Kensington compatible | Yes |
| | Power ON password | Yes |
| Ceiling mount | | Yes |
| Full Function IR Remote Control | | Yes |
| Remote controller range | | 16.40 feet maximum |
| Included Accessories | | Wireless remote controller (YT-35), RGB cable, AV cable, AC Power Cord, Projector Soft Case, Accessory Soft Case, Manual on CD-ROM |
| Optional Accessories | | Replacement Lamp (Part # YL-3B) RS-232C adapter (Part # YK-5) |
| UPC Code | 0-79767-18413-1 | |
| Carton Dimensions | 11.9" W x 7.4" H x 15.4" D | |
| Carton Weight | 8.6 Lbs. | |

* Compliant with ISO 2118-2005

visit: www.superslimprojector.com

CASIO

CASIO is a registered trademark of CASIO Computer Co., Ltd. in Japan. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. WXGA is a registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners. Specifications subject to change without notice.