



ImagePro 8807 Super Bright LCD Projector

- 4000 Lumens Brightness
- XGA Resolution
- 400:1 Contrast Ratio
- Digital Keystone Correction (H&V)
- Auto Ceiling Detection
- Easy Lamp Replacement
- Monitor Loopthrough
- RS232 for Control and USB for Remote Mouse Capability



8807 DUKANE

ImagePro 8807

Super Bright LCD projector

The Dukane ImagePro 8807 is a great value projector for most large venue or high brightness environments.

Outstanding connectivity and enhanced features including automatic ceiling detection and easy lamp replacement make this a great choice for ceiling mounted applications.



Key features:

- XGA (1024 x 768) Resolution
- 4,000 ANSI Lumens of Brightness
- 400:1 Contrast Ratio
- Flexibility with 2 computer and 3 video inputs
- Digital Keystone Correction (H&V)
- Auto Ceiling Detection
- Easy Lamp Replacement
- Monitor Loophrough
- RS232 for Control and USB for Remote Mouse Capability
- PIP Function
- HDTV Compatible
- Two Year Warranty and One Year Peace of Mind Service

8807 Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	24	3.4	4.5
40	32	4.4	5.9
50	40	5.6	7.3
60	48	6.7	8.8
80	64	9.0	11.6
100	80	11.2	14.5
200	160	22.2	28.8
300	240	33.3	43.2

Throw Ratio (distance to width) 1.7 2.2

DUKANE

Dukane Corporation
 Audio Visual Products Division
 2900 Dukane Drive
 St. Charles, Illinois 60174
 800-676-2485
 630-584-5156
 avsales@dukcorp.com
 www.dukcorp.com/av

toll-free
 fax
 e-mail



ImagePro is a registered trademark of Dukane Corporation
 #11697-E-06

Specifications

Image Element	0.99" polysilicon TFT x3, MLA
Brightness	4000 ANSI lumens 3200 (whisper mode)
Resolution	1024 x 768 pixels (H x V), XGA
Contrast	400:1
Scanning Frequency	fh 15-100 kHz, fv 43-120 Hz
Lens	Manual zoom and focus (F=1.7 to 2.4), 1.3X
Lens Throw Ratio	1.7 -2.2 :1 throw distance to image width
Keystone Correction	Digital, vertical +/--15 deg, automatic horizontal +/- 10 deg
Aspect Ratio	4:3, 16:9 selectable
Computer Compatibility	VGA, SVGA, XGA SXGA compressed, MAC
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV 1080i, 1125i, 720p, 525p/i, 625i, 480p
Image Control	Freeze function, electronic magnification and pan, PIP
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	250W
Lamp Life	2000 hours (3000 in whisper mode)
Audio	1W x 2
Throw Distance	40" to 510"
Screen Size, diagonal	30" to 300"
Inputs, Video	(1) Component, RCA x 3 (1) S-video, Min DIN 4-pin, (1) Composite video, RCA x 1 w/ LR RCA Audio
Inputs, Computer	(1) DVI-I (digital RGB) (1) RGB Signal: D-sub, 15 pin Audio, Stereo mini-jack x 2 15 pin, D-sub
Outputs Monitor	Audio, Stereo mini jack x 1
Outputs Audio	9 pin D-sub Connector, RS232C
Outputs,Control	USB connector x 1
Security	Kensington lock slot
Fan Level	39dB, (35dB in whisper mode)
Operating Temperature	41 to 95 deg. F (5-35 deg C)
Power	AC 100-120V, AC220-240V 50/60 Hz, 350 watt
Size (WxHxD)	14.5" x 4.7" x 10.7"
Weight	13 lbs.
Carton Size	17" x 14" x 20
Shipping Weight	25 lbs.
Accessories Included	Remote control, batteries, power cord, S-Video cable, Computer cable, USB cable, Audio/Video cable, Speaker cable, Filter sponge, User Manual, CD ROM, and Soft Carry Case
Safety	UL, cUL, FCC, CE, CB, CCC, UCIC
Optional Accessories	Lamp 456-8807 Wireless Extender, LV3500W Ceiling mount , universal; RPA-U

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

2YR