

HITACHI

Inspire the Next

Performa™ CP-RS55



- 1,500 ANSI lumens
- Native SVGA resolution
- 4.84 lbs
- RGB / Composite / S-video Inputs
- Digital gamma correction
- HDTV theater ready
- FCC Class B
- 16:9 mode
- Vertical keystone correction
- Reverse image function for ceiling mount
- Remote control
- My Memory
- Whisper mode 32dB
- Progressive scan
- Digital zoom (x4)
- Freeze function
- Fixed zoom & manual focus
- Kensington security slot
- My Screen

SPECIFICATIONS

Model name		CP-RS55	
Liquid crystal panel structure		0.55" polysilicon active-matrix TFT x 3	
Number of pixels		480,000 pixels	
Resolution		800 X 600 pixels	
Colors		16.7 million colors	
Aspect ratio		Native 4:3/16:9 compatible	
Lens		F1.65 (fixed), manual focus	
Throw ratio (distance:width)		1.8: 1	
Lamp		165W UHB	
Brightness		1,500 ANSI lumens	
Expected lamp life		Approx. 2,000 hours	
Contrast ratio		300 : 1	
Speakers		1W x 1	
Power supply		AC100-120V/AC220-240V 50/60Hz	
Power consumption		240W	
Operating temperature		32°F ~ 95°F	
Input signals	RGB	VGA, SVGA, XGA/SXGA (Compressed), MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60	
	Component video	480i, 575i, 480p, 1,080i, 720p	
Acoustic noise level		38dB (32dB in whisper mode)	
H sync		15kHz ~ 91kHz	
V sync		50Hz ~ 120Hz	
Vertical keystone correction		Digital keystone +/- 15°	
Approvals		UL, C-UL, FCC Class B, CE, TUV	
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
	Audio	Input	Stereo mini jack x 1
Control terminals			9-pin D-sub connector x 1 (RS-232C control)
Dimensions			11.22" x 2.87" x 7.94" (W x H x D)
Chassis	Weight		4.84 lbs.
	Supplied accessories		Remote Control, Batteries (AA), RGB Cable, Power Cord, Safety Instruction, Quick Start Guide, Users Manual CD-ROM, Lens Cap, Strap, Filter Cover
Replacement parts	Lamp		CPRS55LAMP
	Remote Control		(Part #: HL02151)



Screen Size 4.3		Throw distance
Diagonal*	Width*	
40	32	57
60	48	87
80	64	116
100	80	145
120	96	174
150	120	218
200	160	291

Throw ratio: 1.8:1 (distance:width)

*: Measured in inches

PERFORMA™
CP-RS55 Dimensions
(Incl. protruding part)

