

## LPS130 | SVGA



The LPS 130 is perfectly suited for presentation and home cinema purposes. The projector offers image with the brightness of 1300 ANSI lumens, SVGA resolution (800x600), a contrast ratio of 350:1, D-Sub and Video/S-Video input connectors and a possibility of control with the use of a PC or a remote control. This product is also equipped with the function of automatic detection of the signal source. Home cinema fans will surely appreciate functions of the LPS 130 such as: a 16:9 image format, PIP (Picture in Picture) and a freeze mode.

Technical data	
<b>Diagonal</b>	40" - 200" (distance of projection 1.33 – 6.67m)
<b>Luminosity</b>	1,300 ANSI lumens
<b>Contrast ratio</b>	350 : 1 typical
<b>Display colour</b>	16.77 Million
<b>Horizontal sync</b>	15 - 80 KHz
<b>Vertical sync</b>	43 - 85 Hz
<b>Maximum resolution</b>	1.3 megapixels (1,280 x 1,024)
<b>Native resolution</b>	0.5 megapixels (800 x 600)
<b>Resolutions</b>	832 x 624 / 74 Hz 720 x 400 / 70, 85 Hz 640 x 400 / 70, 85 Hz 1024 x 768 / 43, 60, 70, 75, 85 Hz 800 x 600 / 56, 60, 72, 75, 85 Hz 640 x 480 / 60, 66, 72, 85 Hz
<b>Input connector</b>	D-Sub mini 15 pin, video, s-video, Composite-video
<b>Syncronisation</b>	Composite-, Separate Sync., NTSC, PAL, SECAM
<b>Speaker</b>	2 W (mono)
<b>Audio-signal-input</b>	Mono mini jack , Ø 3,5 mm
<b>Focus</b>	manual focus
<b>Zoom</b>	manual zoom ; 1.23
<b>Source of light</b>	150 W high-pressure mercury lamp
<b>Noise</b>	max. 35 dB
<b>Controls</b>	OSD menu in 8 languages (D, GB, F, RU, JP, ES, I, Ch)
<b>User controls</b>	Auto-Setup, brightness, contrast, phase, clock, horizontal and vertical position, colour temperature (R, G and B controlled independently), vertical trapezoid distortion, zoom, horizontal and vertical image offset, reset, audio signal (volume, bass/treble, mute)
<b>Apple - Mac</b>	All iiyama projectors are compatible with Apple-Macintosh computers.
<b>Warranty</b>	3 years with free transport provided (with the exception of lighting elements)
<b>Safety</b>	TÜV-GS, CE, UL, FCC-B
<b>Power supply</b>	AC 90 – 264V, 50 / 60 Hz
<b>Power usage</b>	max. 210 W
<b>Dimensions w x h x d</b>	233 x 93 x 297 mm
<b>Weight</b>	3.1 kg

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.