

PJ759

**LIGHT, BRIGHT AND
PORTABLE PROJECTOR**
WITH KEYSTONE CORRECTION

Versatile performance leader.

The ViewSonic® PJ759 projector is a performance leader with a rich feature set at an affordable price. The PJ759 delivers 2,600 LUMENS AND 1024x768 XGA RESOLUTION, scalable up to 1600x1200 UXGA, for crisp, detailed images in any lighting situation. With SEVEN PICTURE MODES, including daylight and blackboard, whiteboard, greenboard, you can adjust the light output for any given environment. This versatile projector is easy to set up and its DIRECT OFF FEATURE allows you to unplug it and go. A wide array of PC AND VIDEO CONNECTIVITY OPTIONS let you deliver dynamic, versatile presentations and the easy lamp and filter replacement make maintenance a breeze. The PJ759 is ideal for table-top or mounted use in the office, classroom or on the road.



PORTABLE WITH EASY SET UP

- > **Bright in virtually any setting**
Packs 2,600 lumens in 7.8 pounds. It's the bright choice for mobile presenters.
- > **Quick set up**
Auto vertical keystone correction automatically squares the image for quick set up. The direct off feature lets you just unplug the projector and go.
- > **Enhanced security features**
Security bar and user-assigned PIN code protect your projector from theft and unauthorized use.
- > **Ultimate display source flexibility**
With two RGB inputs you can connect a computer or add a video source for dynamic meetings and presentations.
- > **Easy maintenance**
The sliding filter cover and simple lamp replacement from the top of the unit make maintenance a breeze.
- > **Whisper-mode extends lamp life and reduces noise output**
- > **The best warranty in the business**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJ759

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



PROJECTOR	Type	0.63 Poly-Si TFT with micro-lens
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
DISPLAY	Keystone	Vertical $\pm 15^\circ$
	Size	30"–300" (diagonally)
	Throw Distance	35"–354"
	Throw Ratio	1.5–1.7:1
	Lamp	220W, 2,000 hrs. normal, up to 3,000 hrs. whisper-mode*
AUDIO	Brightness (max)	2,600 ANSI lumens
	Contrast Ratio	500:1
	Aspect Ratio	4:3 (native), 16:9
INPUT SIGNAL	Speakers	1x7W
	Video	RGB analog, NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)
COMPATIBILITY	Frequency	F _H : 31~106kHz, F _V : 56~120Hz
	PC	Analog: from VGA up to UXGA (scaled)
CONNECTOR	Mac®†	Analog: up to UXGA
	RGB (input)	15-pin HD, D-sub (2)
USB	Composite Video (input)	RCA jack (1)
	S-video (input)	Mini-Din 4-pin
	Component Video (input)	VGA DB-15 to component adapter**
	Audio (input/output)	Stereo mini-jack 1-in, 1-out
POWER	For mouse control only	
	Voltage	100–240VAC, 50–60Hz (universal)
CONTROLS	Consumption	320W (typ)
	Basic	Standby, input, reset, V. keystone
OPERATING CONDITIONS	OnView®	Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. phase, H. size, auto adjust, video NR, color space, component, video format, frame lock, computer in, resolution, auto keystone, information, V. keystone, whisper, mirror, volume, speaker, audio, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, source name, auto search, auto on/off, lamp time, filter time, My Button, service menu, security
	Temperature	41–95°F (5–35°C)
	Humidity	10–85% (non-condensing)
	Normal	36 dB (typ)
NOISE LEVEL	Whisper-mode	30 dB (typ)
	Physical (W x H x D)	13.4" x 3.9" x 10.6" (340mm x 100mm x 270mm)
DIMENSIONS	Net	7.8 lb. (3.5 kg)
	Gross	17.0 lb. (7.7 kg)
WEIGHT	REGULATIONS	UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S
	OTHER	Short throw, auto vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control, direct off, low noise (30 dB), unplug and go, white board, black board, green board, daylight mode, adjustable fan speed
WARRANTY	Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running whisper-mode exclusively can extend lamp life. **Optional cables required. ***Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13641-00B-08/07] PJ759-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com