

Dell M410HD Mobile Series Projector

PROJECTION

Brightness:
2000 ANSI Lumens (Max.)
Contrast Ratio:
2100:1 Typical (Full On / Full Off)
Resolution:
WXGA (1280 x 800)
Uniformity:
85% Typical (Japan Standard - JBMA)
Projection Lens:
F-Stop: F/2.5~2.67
Image Size:
27.2" ~ 361" (diagonal)
Projection Distance:
1m ~ 12m
Set Up:
3D - Enabled

CONNECTIVITY

Power: AC power input socket
Computer Input: one D-sub for analog/RGB component, HDTV input signals
Computer Output: NA
Video Input: one composite video RCA and one S-video
USB Input: one USB slave for remote support and firmware upgrade
Audio input: one phone jack (Diameter 3.5mm)
HDMI Input: one HDMI 1.3 (HDCP compliant)

LAMP

Lamp Life Cycle³:
Up to 3000-hour Typical
Up to 5000-hour Eco-Mode
Lamp Type:
OSRAM E17.6 165W user-replaceab

VIDEO COMPATIBILITY

S-Video/Composite Video: NTSC [J, M, 4.43, supports Closed Captioning (CC1~CC4)], PAL (B, D, G, H, I, M, N, Nc, 60), SECAM (B, D, G, K, K1, L)
Component Video (via VGA) & HDMI (HDCP Compliant) -480i/p, 576i/p, 720p, 1080i/p

AUDIO

Multimedia Audio: 1W Speaker Mono

KEYSTONE CORRECTION

Vertical: +40° / -35°
Horizontal: N/A

COLOR, SIZE AND WEIGHT

Dimensions (W x D x H):
8.07" x 6.10" x 2.99"(205 x 155 x 75.9mm)
Weight:
2.6 lbs (1.18 kg))

Environmental and Regulatory

ELECTRICAL

Power:

Universal AC 100-240 50-60Hz with PFC input

Power Consumption Operational:

Normal mode: $210W \pm 10\%$ @ 100Vac

Eco mode: $166W \pm 10\%$ @ 110Vac

Power saving mode: less than 12W

Standby mode: less than 1W

ENVIRONMENTAL

Operating temperature:

$5^{\circ}C - 35^{\circ}C$ ($41^{\circ}F - 95^{\circ}F$)

Humidity:

80% (maximum)

Storage temperature:

$0^{\circ}C - 60^{\circ}C$ ($32^{\circ}F - 140^{\circ}F$)

Humidity:

90% (maximum)

Shipping Temperature:

$-20^{\circ}C - 60^{\circ}C$ ($-4^{\circ}F - 140^{\circ}F$)

Humidity:

90% (maximum)