

# PJ402D

## LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

## Easy to use, easy to afford.

The ViewSonic® PJ402D DLP® projector delivers excellent performance and outstanding value. This powerful projector packs 2,000 LUMENS INTO JUST 4.6 POUNDS and displays SHARP, BRILLIANT, HIGH CONTRAST DATA AND VIDEO thanks to the digital technology of DLP. Its lightweight package makes it easy to take from one meeting room to another, from work to home, or on the road. MOTION ADAPTIVE DEINTERLACING, DIGITAL KEYSTONE CORRECTION and OnView® controls ensure a perfect image every time. The PJ402D supports HD signals and allows you to connect a computer or other video source for dynamic meetings and presentations. It's the ideal choice for users who desire an easy-to-use, portable projector at a great price.



### OUTSTANDING PRESENTATIONS

- > **Bright in virtually any setting with 2,000 lumens**  
Packs 2,000 lumens in just 4.6 lbs. It's the bright choice for mobile presenters.
- > **DLP® technology**  
Stunning all digital clarity delivers lifelike color, sharp graphics, and outstanding video.
- > **Ultimate video source flexibility**  
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**  
Capable of displaying HDTV signals as well as other video and data sources\*.
- > **Advanced video features**  
Motion adaptive deinterlacer for superior video performance.
- > **Whisper-mode extends lamp life**  
Extend the life of your lamp up to 4,000 hours\*\* and reduce noise output.
- > **OnView® controls for superior screen adjustability**  
Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.
- > **The best warranty in the business**  
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.\*\*\*



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

# PJ402D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



## Optional Accessories

- Replacement lamp . . . . .RLC-014
- Hard case with wheels . . . . .PRJ-HCA-001
- Extended Express Exchange® . . . . .PRJ-EE-05-03
- Soft case with wheels and laptop bag . . . . .PRJ-SCA-004
- Universal ceiling mount kit . . . . .WMK-005
- VGA to component video adapter . . .ADPT-002

<b>PROJECTOR</b>	Type	0.55" DDR DMD, DLP®
	Pixel Format	800x600 SVGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
<b>DISPLAY</b>	Size	27.8"–277.8" (diagonally)
	Throw Distance	47.3"–393.6"
	Throw Ratio	1.79–2.1:1
	Lamp	200W, 2,000 hours**
	Brightness	2,000 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3 (native), 16:9
<b>AUDIO</b>	Speakers	1x2 watts
<b>INPUT SIGNAL</b>	Computer and Video	NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 576p, 720p, 1080i)
	Frequency	F <sub>H</sub> : 31–79kHz; F <sub>V</sub> : 50–85Hz
<b>COMPATIBILITY</b>	PC	Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
<b>CONNECTOR</b>	RGB (input)	15-pin HD, D-sub cable (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	VGA DB-15 to HDTV/component cable*
	Audio (input)	Stereo mini-jack (x1); RCA (L/R)
<b>POWER</b>	Voltage	100–240 VAC, 50/60Hz (universal)
	Consumption	250W (typ)
<b>CONTROLS</b>	Basic	Standby/On, input, menu
	OnView®	Display mode, brightness, contrast, keystone, aspect ratio, blank screen, gamma, white peaking, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (auto source select, rear, ceiling, eco mode), lamp hours, lamp reset, auto shutdown, OSD timeout, menu position, factory reset), audio (audio, mute)
<b>OPERATING CONDITIONS</b>	Temperature	41–95°F (5–40°C)
	Humidity	35–85% (non-condensing)
<b>NOISE LEVEL</b>	Normal	36 dB (typ)
	Whisper mode	34 dB (typ)
<b>DIMENSIONS (W x H x D)</b>	Physical (mm)	256mm x 88mm x 200mm
	Physical (in.)	10" x 3.8" x 7.9"
<b>WEIGHT</b>	Net	4.6 lb. (2.1 kg)
	Gross	11.0 lb. (5.0 kg)
<b>REGULATIONS</b>		UL, FCC-B, CCC, CE, NOM, PSB
<b>OTHER</b>		Vertical digital keystone correction, 3:2 pull down, whisper mode
<b>PACKAGE CONTENTS</b>		Projector, power cords, VGA cable, RCA video cable, S-video cable, audio mini-cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide
<b>WARRANTY</b>		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp:***

**ViewSonic®** 

*the choice of professionals*

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Optional cables required. \*\*Running whisper-mode exclusively can extend lamp life. \*\*\*See ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12758-00B-01/06] PJ402D-1

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)