

LE-5W BK

See Other Portable Projectors 

Portable Projector
Item Code: 8483B002

Specifications

Main Unit Spec

Projector Specifications

Imaging Device	0.45" DLP Panel
Aspect Ratio	16:10
Native Resolution	1280 x 800
Brightness	500 Lumens
Contrast Ratio	3000:1
Digital Keystone (Vertical)	±40 degrees (Auto/Manual)
Optics	
Throw Ratio	1.2:1
Image Adjustments	
Mounting	Ceiling / Rear-Ceiling
Tilt Angle	0 to 6 degrees
Input Signals	
Scanning Frequency	H-Sync: 31-102MHz, V-Sync: 23-120MHz
Analog PC Input	WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
Digital PC Input	WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
Video/S-Video Input	NTSC / NTSC4.43 / PAL / SECAM / PAL-M / PAL-N / PAL-60
Component Input	1080p / 1080i / 720p / 576p / 576i / 480p / 480i
Digital Video Input	1080p / 1080i / 720p / 576p / 576i / 480p / 480i

Terminals

(Input) RCA x1

(Input) Stereo Mini Jack

(Output) Stereo Mini Jack

Built-in Speaker

Lamp

Lamp Type

Lamp Life

Remote Control

Sensor

Ratings

Fan Noise (Quiet/Normal)

Power Consumption
(Normal/Quiet/Stand-By)

Power Voltage

Temperature Operating

Dimension (WxHxD)

Weight

Warranty

Composite Video Input

Stereo Input x1

Stereo Output x1

2.5W x2 (Stereo)

Luminus PT-54 R, G, B LED

20,000 Hours

Wireless Infrared

38dB (Normal) / 32dB (Power Saver)

130W (Normal) / TBD (Power Saver) / 0.5W
(Standby)

AC 100 ~ 240V, 50/60Hz

32° to 104° F (0° to 40° C)

9.8 x 1.8 x 7.6 in. (248 x 45.3 x 193mm)

3.5 lbs. / 1.6 kg.

3 years limited parts and labor

[BACK TO TOP ▲](#)