

Elegant and electrifying, the LightStyle LS-5 is Runco's first-ever 1080p projector designed for both performance and esthetics. Where sleek design encompasses incredible performance, this stylish combination of legendary Runco engineering and impactful design yield a powerhouse that elevates the bar for affordable home theater projection.

Light
STYLE



LightStyle LS-5 Specifications

Projector Type:	Digital Light Processing™ (DLP™), Single-Chip, 16:9 SuperOnyx™ DMD™
Native Resolution:	Full HD, 1920 x 1080
Aspect Ratios:	Native (Pixel-to-Pixel), 16:9, Letterbox, 4:3, 4:3 narrow, Letterbox
Video Standards:	HDMI and DVI with HDCP for digital video, Component and RGB HDTV (1080p, 1080i, 720p), Component and RGB EDTV (576p, 480p), Component, Composite and S-Video SDTV (576i, 480i), RGB SCART with adapter, NTSC (M,4.43), PAL (B,G,H,I,N,M), SECAM (M)
DTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i 50/60, 1080p 24/50/60, 1080PSF
Picture Size (16:9 screens):	Recommended Width: 72 – 96 in. Maximum Width: 120 in.
Throw Distance Factor x Screen Width:	1.85 – 2.40 (distance/width) – Standard lens, 1.56 - 1.86 (distance/width) - Optional short-throw lens
Horizontal and Vertical Offset	-50% to +120% (vertical, ceiling mounted, % of the half height)
Light Output:	CSMS** Specifications: Home Theater Calibration: 754 ANSI Lumens; 48 Foot-Lamberts (fL); 1000 ANSI Lumens*
Contrast Ratio:	CSMS** Contrast Ratio: 481:1; 15,000:1 typical (sequential)*
Lamp:	180W (230W High Power Mode) (selectable)
Lamp Life:	4000 hour lifetime*
Inputs:	(2) HDMI w/1.3 HDCP; (1) Component (3 x RCA gold); (1) RGB (HD15); (1) S-video (4-pin mini DIN); (1) Composite (RCA, gold); (1) 3.5 mm mini jack; (1) 9-pin D-sub
12V Output:	(1) 3.5 mm mini jack
Power Requirements:	100V - 240V at 50-60Hz (auto-ranging), true soft power
Operating	50° F (10° C) - 104° F (40° C)