## **BumbleBee**



## **BRIGHTNESS**

150 ANSI Lumens (28" diagonal)

RESOLUTIOI

800x600 native

1280x1024 compressed

DISPLAY TYPE

Single 0.55 12° DDR DMD

CONTRAST RATIO

1000:1

**ASPECT RATIO** 

4:3 Native

16:9 Compatible

LAMF

**OSRAM Ostar LED Module** 

LAMP LIFE

10,000 hours

DIAGONAL IMAGE SIZE

12" - 60" inches

PROJECTION LENS

Fixed zoom with focus adjustment



**Extended Warranty** 

Battery Pack

**Composite Video Cable** 

Remote



Special features of the **BumbleBee** include:

**Ultra Portable**—Weighing in at 1 lb—this tiny 'Bee' can be taken anywhere!.

**LÉD Lamp**—A 10,000 hour lamp life will last for years and years. **SD Card Slot**—Versatility for ultimate presentations and slide shows on the go.

**Rechargeable Battery**—Connect to power or run from a battery. Use it outside or where power isn't available.

SHIPS WITH:
User Manual
AC/DC Adaptor—Power Cord
Composite Video Cable
Remote Control
Soft Nylon Case

## THROW DISTANCE

1.3' - 6.6' feet

40 - 200 cm

**THROW RATIO** 

1.32:1 (fixed lens)

INPUI

Audio in

Component

Composite Video

S-Video

SD Card

**VGA** 

OUTPUTS

Audio out

COMPATIBILITY

VGA, SVGA, XGA, SXGA, Mac

KEYSTONE

+/- 15° vertical

VIDEC

NTSC, PAL, SECAM

DWP CONSUMPTION

30 W Standard mode

HDTV / EDTV / SDTV

480p, 720p, 1080i

AUDIO

1 X 0.3 watt speakers

**DIMENSIONS (WxDxH)** 

4.7" x 1.8" x 3.8" inches

121 x 47 x 99 mm

WEIGH1

1.0 lbs without battery

2.0 with battery

DECIBEL RATING

30 dB

WARRANTY

2 year parts & labor

ECC CERTIFICATION

Class B

**POWER SUPPLY** 

100-240 AC 50-60 Hz



19462 Powder Hill Place, Suite 101 Poulsbo, WA 98370