

Specifications

Part Number: S5201M Acer S5201M Projector

Following are the specifications for the Acer S5201M projector series.
Specifications are subject to change without notice or obligation.

Feature	Specification
Projection System	DLP®
Display Panel	0.55" DarkChip™ 3 DMD Native: <ul style="list-style-type: none">• 1,024 x 768 (XGA)
Resolution	Maximum: <ul style="list-style-type: none">• 1,600 x 1,200 (UXGA)• 1,920 x 1,080 (1080p)
Video Compatibility	NTSC (3.58/4.43) PAL (B/D/G/H/I/M/N) SECAM (B/D/G/K/K1/L) HDTV (720p, 1080i, 1080p) EDTV (480p, 576p) SDTV (480i, 576i) Native: <ul style="list-style-type: none">• 4:3
Aspect Ratio	Supported: <ul style="list-style-type: none">• 4:3• 16:9
Contrast Ratio	4,500:1
Displayable Colors	1.07 Billion Colors
Brightness	3,000 ANSI Lumens (Standard) 2,400 ANSI Lumens (ECO)
Projection Lens	F = 2.6, f = 7.5mm Manual Focus

Projection Screen Size (Diagonal)	40" ~ 300" (102cm ~ 762cm)
Projection Distance	1.6' ~ 12.2' (0.5m ~ 3.7m)
Throw Ratio	77" @ 95cm (0.61:1)
Horizontal Refresh Scan Rate	30k ~ 100k Hz
Vertical Refresh Scan Rate	50 ~ 120 Hz
Lamp Type	Osram 230 W user replaceable P-VIP lamp
Lamp Life	2,500 Hours (Standard) 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical), Manual
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	Yes
Audio	10 watts speaker (Two internal speaker with 5 watts output)
Weight	7.7 lbs (3.5 Kg)
Dimensions (W x D x H)	11.4" x 10" x 3.9" (290 x 254 x 99 mm)
Remote Control	IR remote control with laser pointer and Page Up / Page Down functions
Zoom	Digital: 2X
PIP	None
Lens Shift	None
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	352 Watts (Operation), <1 Watts (Standby, LAN off)
Operating Temperature	41°F ~ 95°F (5°C ~ 35°C)
Operating Humidity	80%RH (Max.)
Noise Level	33 dBA (Standard mode) 28 dBA (ECO mode)
I/O Connectors	Input: <ul style="list-style-type: none"> • Analog RGB/Component Video (D-sub) x 2 • Composite Video (RCA) x 1 • S-Video (Mini DIN) x 1 • HDMI (Video, HDCP) x 2

	<ul style="list-style-type: none"> • PC Audio (Stereo mini jack) x 2 • USB (Type A) x2 • USB (Mini-B) x1 • Mic In (Stereo mini jack) x 1 <p>Output:</p> <ul style="list-style-type: none"> • Analog RGB (D-sub) x 1 • PC Audio (Stereo mini jack) x 1
--	---

Control Interface
 USB (Mini-B) x 1
 RS232 (Mini DIN) x 1
 12V DC (Screen control) x 1

Network Interface
 Ethernet port (RJ45) x1

Other Features
 Acer ColorBoost Technology
 Acer ColorBoost II Technology
 Acer ColorBoost II+ Technology
 Acer SmartFormat Technology
 Acer EcoProjection Technology
 ColorSafe II
 Empowering Key
 Acer eTimer Management
 Acer eOpening Management
 Acer eView Management
 Wall-Color Compensation
 Acer ePower Management
 High Altitude Mode
 Acer Top-Loading Lamp Design
 Installation Menu
 Digital Connectivity-HDMI™
 Dual D-Sub Input
 Multi-PC Connectivity
 Instant Pack
 Auto Shutdown
 Quick Start
 Quick Detection
 Smart Detection
 PIN Security
 Digital Zoom and Pan
 ECO Mode
 Loop Through
 Alarm
 Built-in Speaker
 RS-232

40° Vertical Keystone Correction
3X Color Wheel Rotation Speed
Closed Captioning
Instant Resume
DLP 3D ready
True 24p
Interactive Projection
USB Slide Show
Crestron Network Control (LAN & Wireless)
Remote Desktop
Smartphone Projection (MobiShow), w/o HD Video
(Optional)
Plug & Show (PnS) Token (Optional)

Accessories

AC power cord
VGA cable
Composite video cable
USB Cable
Acer SmartPen
Remote control
Battery x 2 for remote control
Lens cap
Carrying case
User's guide (CD-ROM)
Network/Multimedia guide (CD-ROM)
NXBoard application (CD-ROM)
Quick start guide
Security card