NEVER CHANGE A MERCURY LAMP AGAIN! YOU COULD SAVE UP TO \$800.*



Eco Friendly, Bright, Lightweight and the Thinnest High Brightness Projector in the Industry, 1.7 Inches Thick!**

MERCURY LAMP FREE ADVANTAGES

- 10X Longer Light Source Life than Casio mercury lamp
- Economical, mercury vapor replacement lamps can cost up to \$400.00
- More consistent brightness and color compared to mercury lamps
- Quick-on—As quick as 8 Seconds
- Instant-off—No Cool Down Time

VALUE AND A GREAT WARRANTY

- 3 year warranty on the projector and 3 years or 6,000-hour usage on the light source
- Visit: www.greenslimprojector.com for complete warranty details





USB MODELS ONLY

USB 2.0 High Speed Wireless LAN IEEE802.11b/g/n Adapter Available and sold separately







Presentations from your USB Thumb Drive*** without a PC

SUPER COLOR

- Hybrid light source results in more than double the color spectrum compared to previous Casio mercury lamp projectors
- The new hybrid technology results in superior color reproduction and brightness



ENVIRONMENTALLY FRIENDLY

- Mercury free
- Long lamp life reduces electronic waste
- · Low power consumption



2X OPTICAL ZOOM

 Whether you are in a small office or a large boardroom the 2X power zoom lens gives you the flexibility to easily position the projector



WIDESCREEN MODELS ONLY

Match up to your Widescreen Laptop or great for playing games







Specifications

BRIGHTNESS	XGA	XGA WITH USB	WXGA	WXGA WITH USB
2000	XJ-A130	XJ-A135U	XJ-A230	XJ-A235U
2500	XJ-A140	XJ-A145U	XJ-A240	XJ-A245U





2000	1/0 /1140	/\u071400	70 72	-40 70 7
BASIC SPECIFICA	TIONS			

BASIC SPECIFICATIONS				
Contrast ratio	Telephoto mode	1800:1		
Projection lens		2X Power zoom & focus		
Lens offset		XGA: 100% WXGA: 84%		
Light Source		Laser & LED hybrid technology		
Estimated Operating Life Projection screen size		Up to 20,000 hours (waranty 3 years or 6,000 hours—Visit:		
		www.Greenslimprojector.com for complete warranty details		
		15 ~ 300-inch		
Projection range	60-inch screen	XGA: 5.6 ft ~ 11.2 ft WXGA: 4.62 ft ~ 9.24 ft		
1 Tojection range	100-inch screen	XGA: 9.24 ft ~ 18.48 ft WXGA: 7.92 ft ~ 15.84 ft		
	Minimum	2.77 ft		
	Projection ratio	XGA: 1.4-2.8:1 WXGA: 1.15-2.30:1		
Projection system		DLP® system		
Display element	Device type	XGA: 0.55-inch DLP® chip WXGA: 0.65-inch DLP® chip		
	Native Resolution	XGA (1024 x 768) 786,432 pixels		
		WXGA (1200 x 800) 1,024,000 pixels		
	Native Aspect Ratio	XGA: 4:3 WXGA: 16:10		
Color reproduction	·	Full color (16.77 million colors)		
Power source		AC100~240V, 50/60Hz		
Keystone correction	Auto	+30° Vertical		
Reystorie correction	Manual	±30° Vertical		
Dimensions	Iviariuai	11.69" x 8.26" x 1.69" incl. projections		
Dimensions				
		1.58" (at thinnest point excl. projections)		
Weight		5.0 lbs		
Ceiling mount		Yes (mount available separately from 3rd party vendors)		
Power consumption	Operating	270W (Eco Off)/190W Eco On Level 1)/130W(Eco On Level 2)		
	Standby	100 - 120V (0.4W), 220 - 240V (0.6W)		
Security Compatibility	Kensington compatible	Yes		
	Power ON password	Yes		
INTERFACE TERMINALS				
RGB/Component		mini D-Sub 15 pin x 1		
Video Input		Also use as YCbCr/YPbPr input		
Native Resolution		XGA (1024 x 768) 786,432 pixels		
Native Resolution				
		WXGA (1200 x 800) 1,024,000 pixels		
Computer Signal Compatibility	(max.)	UXGA (1600 x 1200) (Compressed)		
Resolutions		SVGA, XGA, WXGA, SXGA, SXGA+, WXGA, WSXGA+, UXGA		
Digital input		HDMI x 1 (480P ~ 1080P)		
Audio	Input	3.5mm mini-jack		
	Output	1 W speaker		
	·	3.5mm mini-jack (shared with Audio Input)		
Video	Input terminals	Composite: 3.5mm mini-jack		
		(sharing audio terminal), YCbCr/YPbPr		
Video Signal	Video Systems	NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM/YcbCr/YPbPr		
Compatibility	DTV/HDTV	480i/480P/576i/576P/720P/1080i/1080p		
Control	Terminal	RS-232C		
		Adapter cable (YK-5) required and sold separately		
Wireless capability (USB Models only)		Optional (YW-3) 802.11 b/g/n adapter required and		
		sold separately		
USB Models Only		TypeA x 1, USB (2.0) Host		
	Connectable	Multi-functional camera system YC-400/430 (Not Included)		
	Equipment	USB memory (commercially available) (Not Included)		
		CASIO's Digital Camera/Graphic calculator/		
		Electronic dictionary (Not Included)		
OTHERS				
Usage environment	Operating temperature	41~95°F		
osage environment				
	Operating humidity	20~80% (non-condensation)		
D	High Altitude Mode	Yes (for operation 3,300~6,600 ft)		
Remote controller range		16.5 ft maximum		
Limited Warranty		3 years Parts and Labor plus 3 years or 6,000 hour light source, see Warranty Statement included with product for complete details		
Included Accessories (All Models)		Wireless remote control, RGB cable, AV cable, AC Power Cord,		
, , ,		Projector & Accessory Soft Case, Manual on CD-ROM and booklet		
Included Software (USB Models only)		Wireless Connection 3/EZ-Converter FA/ArcSoft Media		
moladed dollware (OOD Models Offly)		Converter 3 for CASIO Projector		
		YW-3 (Wireless 802.11b/g/n adapter)		
Optional Accessories				
Optional Accessories		VK-5 (RS-232C adapter)		
Optional Accessories		YK-5 (RS-232C adapter)		
		YK-CASE01 (Soft Carry Case with handle and shoulder strap)		
Optional Accessories Shipping/Packing Information	Carton Dimensions Carton Weight			

