

PowerLite® Pro G5450WUNL

MULTIMEDIA PROJECTOR



Brilliant, full HD WUXGA resolution and precision control.

The Epson PowerLite Pro G5450WUNL offers the ultimate projection solution for any auditorium or boardroom, even in ambient light. It ensures amazing image quality with 4000 lumens color/white light output,¹ Full HD WUXGA (1920 x 1200) resolution and C²Fine™ technology. Engineered to integrate with both IP and RS-232, the G5450WUNL works with industry-leading devices, allows easy remote monitoring and control functions using Epson's Easy Management® software and is also compatible with Crestron's RoomView. The features DICOM simulation mode for training and educational purposes and closed captioning decoder.

Bright, Full HD performance — crystal-clear images with WUXGA resolution and C²Fine technology, plus 4000 lumens high color/white light output¹

Complete networkability — wired and wireless (optional) Crestron RoomView compatible network connection, content over IP and message broadcasting

Enhanced connectivity — HDMI, DVI-D, VGA and multiple video/audio inputs **Multi-screen options** — project two side-by-side images from different inputs, or up to four images from network users

Five lens options — interchangeable bayonet lens options, including short-throw, long-throw and rear-projection; plus horizontal/vertical lens shift for flexible setup configurations

PowerLite® Pro G5450WUNL

MULTIMEDIA PROJECTOR

The best-selling projectors in the world.

Epson understands business and education and has a solution no matter what your situation. Built with image quality and reliability in mind, Epson projectors enhance communication and inspire collaboration, while offering a low total cost of ownership. From long-throw projectors to ultra-short-throw and all-in-one solutions, Epson has the model made for you.




Brilliant image quality

3LCD technology — for quality and color that's beyond amazing

- 3 chips for full-time, vibrant color
- 25% less electricity required per lumen of brightness when compared to 1-chip DLP projectors²
- Over 20 years of road-tested reliability built into every projector







Advanced sharpness

Another feature Epson has transferred over from its industry leading home cinema projectors — advanced sharpness for video. Depending on the content, user can adjust any of the following attributes of the image depending on the content: thin line enhancement, thick line enhancement, vertical line enhancement or horizontal line enhancement.

Amazing color light output

Rich color and detail are critical for presentations — that's why it's important to understand that color light output is an essential ingredient in achieving optimum performance. The PowerLite Pro G5450WNL delivers 4000 lumens of color light output and 4000 lumens of white light output¹ for bright, vibrant colorful images.

C²Fine[™] technology delivers a higher contrast ratio

C²Fine offers smooth, uniform images with exceptional contrast for better image quality. Based on this new phase-compensation technology, light leakage is eliminated, and, when combined with auto iris, it allows for contrast ratios of up to 2000:1.





▲ With C²Fine

▲ Without C²Fine

Enhanced connectivity

The PowerLite Pro G5450WUNL is equipped with:

- Full digital connectivity with HDMI port
- 5 BNC, 2 video/audio, 2 x VGA and RS-232 for additional flexibility

Better Products for a Better Future®

For more information on Epson's environmental programs, go to eco.epson.com

Eco Features

- Energy-efficient 3LCD light engine
- Designed to be recycled³
- Epson America, Inc. is a SmartWaySM Transport Partner⁴



Full-featured performance

DICOM simulation mode

DICOM (Digital Imaging and Communication in Medicine) is a standard for handling, storing, printing and transmitting medical imaging information. The projector's DICOM Simulation Mode enables users to reproduce images with an advanced grayscale level that simulates DICOM Part 14. This mode is ideal for viewing grayscale medical images, such as X-rays, for training and educational purposes.²






▲ Normal Mode

▲ DICOM Simulation Mode

6-axis color adjustment

For special projection material such as high-quality photographs or artwork, users can adjust the hue, saturation and brightness for six colors, RGBCMY (Red, Green, Blue, Cyan, Magenta, Yellow).




Improved video with 3:2 and 2:2 pull-down options

3-2 pull-down creates 60 frames per second and 2-2 pull-down creates 48 frames per second from 24 frames, as shown in the chart.


3-2 pull-down: The image is smoother.

2-2 pull-down: The one frame length is the same as film. It is ideal for movies.



Test patterns

The PowerLite Pro G5450WUNL also features four test patterns for precise setup, including detecting distortion, checking linearity, color reproduction and bleeding, and DICOM simulation mode.



Advanced control, monitoring and communication

Epson's EasyMP® monitor tool

If you are searching for a solution that gives you control over your time, Epson network projectors with Easy Management® capabilities can help. Epson networked projectors contain built-in remote access, with no licensing fees added, to utilize the Epson monitor software. These features also give you control, with the ability to troubleshoot and monitor all Epson networkable projector from any PC computer over a wired or wireless Ethernet network.

Additional features to assist administrators/Help Desk

- Remote access and control through the network
- Remote monitoring of up to 1024 Epson networked projectors
- Simultaneously view status, including input sources, power on/off, lamp life hours and more
- Preventative maintenance features, including temperature levels and error alerts
- Schedule (filter and lamp time settings)
- E-mail notification (SMTP) to send alerts to your handheld device
- Enterprise SNMP plug-in available





Network projection — content over IP

You can use EasyMP Network Projection to project your computer screen through the projector via a network for effective meetings, presentations and digital signage applications. You can use either wired or high-security wireless LAN connections and project the same or up to four different images on up to four projectors, or display a panoramic image.

Full networkability

Epson networked projectors can also be accessed from your browser via an internal web page. Whether you assign a static IP address or enable DHCP, the projector becomes accessible once it's integrated in your network. The internal web page lets you control items such as network configuration, projector settings and e-mail alerts.



Message broadcasting

This innovative feature enables you to broadcast customized images/alerts over the network for announcements or instructions. Messages can be sent to up to 1024 projectors simultaneously and will overwrite the current screen content if the projector is being used, unless this function is disabled by the presenter. If the projector is off, message broadcasting will turn the projector on and then display the message.



Powerful content management

Split Screen

Split Screen allows you to display content from two inputs simultaneously, side by side, on a single screen with the following features:

- Three layout options, as shown below
- Video and presentation materials displayed simultaneously
- The ability to run video on both screens



Layout Option-1: 50-50% Split Screen




Layout Option-2: Main image on the left




Layout Option-3: Main image on the right

Multi-PC projection

Epson Multi-PC Collaboration utility allows you to display four individual PC screens simultaneously over the network with another 12 users connected to the same projector on Standby mode. You can drag and drop participants into or out of one of the four quadrants. This feature is a great tool for meetings or classroom projects where multiple users want to present and compare their screens. You can also connect up to four remote projectors at the same time and show the same multi-screen image — another great tool for remote meeting setups.





Easy and flexible installations

Centered lens design

With lens-to-screen alignment, the PowerLite Pro G5450WUNL makes installation easy to plan. Installers can position the ceiling mount, screen and projector independently of one another, knowing that the center of the screen will align with the lens at the center of the projector.




Five lens options

With a 1.6x standard lens (not included), the PowerLite Pro G5450WUNL offers remarkable placement flexibility. For even greater flexibility, Epson offers a total of five lenses with varying ranges including a rear-throw lens. This allows users to choose the motorized lens most suited for their environment. A quick release lever allows for a quick, easy lens exchange.

Off-axis, flexible installation

The Pro G5450WUNL also features a ±30-degree tilt operation for off-axis positioning flexibility. As a result, the G5450WUNL can be used for a wide range of applications, such as projecting on angled surfaces. Epson technology keeps the projector running without compromising performance or causing overheating.




Keystone correction

Adjusts up to ±30 degrees vertically and ±20 degrees horizontally to easily achieve a perfect square image.




Epson lens shift technology

In addition to added reliability and amazing color performance, Epson's industry-leading 3LCD technology enables these projectors to achieve a wide range of lens shift capabilities, allowing you to install around obstacles. This lens shift technology enables an incredible range of ± 58 percent on the vertical axis and ± 9 percent on the horizontal axis.



Quick Corner®

This innovative feature allows you to move any of the four corners of an image independently at setup, using the remote control to adjust each corner for a perfectly rectangular picture. Quick Corner also makes life very easy when setting up a stacked 3D projector solution for education and entertainment. All you need to do is to project the first image and then adjust the corners of the second image to perfectly match the first one.



Low cost of ownership

Long-life lamp that's easy to replace

This high-efficiency lamp lasts up to 2,000 hours in Normal Mode and up to 3,000 hours in ECO Mode.⁶ It can be replaced quickly and easily, without having to uninstall the projector from the ceiling.



Long-life electrostatic air filter


This innovative filter was designed to protect the optical engine, lamp and electronics from small dust particles that can enter any projector. It has a recommended 3,000-hour filter cleaning schedule⁷ and can capture particles as small as three microns, due in part to its pleated, expanded design.



Built-in 7 W speaker

• For multimedia applications — convenient built-in speaker

Built-in closed captioning





- Delivers important content when audio broadcasting is not preferred
- Helps save money no need to pay for an additional decoder and its installation
- Effective and easy to use easily enabled or disabled through the projector remote or menu








PowerLite® Pro G5450WUNL

Multimedia Proiector

Product Name PowerLite Pro G5450WUNL Genuine Epson Lamp Replacement Air Filter

Product Code V11H346920 0 10343 88316 1 V13H010L62 0 10343 88122 8 V13H134A17 0 10343 86897 7



RCA-Audio/Video

Specifications

Projection System

High-aperture Epson 3LCD, 3-chip technology

Projection Method

Front/rear/ceiling mount **Driving Method**

Epson Poly-silicon TFT Active Matrix

Pixel Number

2,304,000 pixel x 3 LCDs (1920 x 1200)

Native Resolution

1920 x 1200 (WUXGA)

Resize

640 x 480, 800 x 600, 1280 x 1024,

1400 x 1050, 1600 x 1200 **Aspect Ratio**

Supports 4:3, 16:9, 16:10 **Pixel Arrangement**

Cross stripe

Color Light Output¹ 4000 lumens

White Light Output¹

4000 lumens (ISO 21118 standard)

Contrast Ratio (High Brightness, Dynamic Mode)

Brightness Uniformity (typical)

Color Reproduction

16.7 million colors

Size (projected distance) 30" - 300"

Lens Shift

Vertical: ±58 degrees Horizontal: ±9 degrees

Keystone Correction Vertical: ±30 degrees

Horizontal: ±20 degrees

Lamp Type

275 W UHF

Lamp Life 2000 hours (Normal Mode)

3000 hours (ECO Mode)

Effective Scanning Frequency Range

Pixel Clock

13.5 MHz - 162 MHz (up to UXGA 60 Hz) Horizontal

15 kHz - 92 kHz

Vertical 50 Hz - 85 Hz

Video I/O

Display Performance

NTSC: 560 line

PAL: 560 line

(depends on observation of the multi-burst pattern)

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/

PAL60/SECAM/480i/576i/480p/576p/720p/

1080i/1080p

Pixel works: video chip 3D Y/C separation, noise reduction

motion compensated

Interlace-Progressive conversion

(2-2.3-2 film detection)

Interfaces HDMI x 1

DVI-D x 1

Computer: D-sub 15pin x 1

Video-1: 5-BNC x 1 Video-2: RCA x 1

Composite video: BNC x 1

S-Video x 1

Audio-in: Mini stereo x 3

Audio-in: RCA (L&R) x 1

Network: RJ-45 x 1, 100 Mbps USB Type-A x 1

Serial: RS-2320

Hardwire Remote jack x 1

Monitor-Out: D-sub 15pin x 1

Projection Lens

Manual focus/zoom

F-number

1.65 - 2.55**Focal Length**

21.28 mm - 37.94 mm

Zoom Ratio

Optical zoom 1.0 - 1.8 Throw Ratio Range

1.30 - 2.36

Other Features

Operating Temperature

32 ° to 104 °F (0 ° to 40 °C)

Power Supply Voltage

100 - 240 V ±10%, 50/60 Hz AC

Power Consumption

413 W (Normal Mode)

345 W (ECO Mode)

10 W Standby (Communication on) 0.38 W Standby (Communication off)

Fan Noise

35 dB (Normal Mode)

30 dB (ECO Mode)

Security

Security cable hole, lens lock, Kensington® lock provision

Dimensions (W x D x H)

Including Feet (with standard lens)

18.5" x 12.26" x 5.96

Excluding Feet, Lens

18.5" x 12.26" x 5.31 Weight 15 lb

Remote Control

Features

Power, source search selection, computer, video, AV mute, freeze, user ID, auto, aspect, color mode, num, page up and down, E-zoom. volume. heln. menu, enter, esc and pointer functions

Operating Angle

Right/left:

Front: ± 60 degrees Rear: ± 30 degrees

Upper/lower:

Front: ± 20 degrees

Rear: +10 to +45 degrees

Operating Distance

Support

The Epson ConnectionSM

Pre-sales support U.S. and Canada

800-463-7766

Internet website www enson com Service Programs

Two-year limited warranty, Epson Road Service program, Epson PrivateLine® dedicated toll-free support (U.S. and Canada only) and 90-day limited

lamp warranty What's In The Box

PowerLite Pro G5450WUNL projector, power cable, computer cable (VGA), projector remote control with batteries, user manual CD, EasyMP software CD, Quick Setup Sheet, PrivateLine support card, registration card, password protection sticker and

Accessory Part Numbers

V13H010L62 Genuine Epson lamp Replacement air filter V13H134A17 V12H306P11 Wireless LAN 802 11 module V12H004S05 Standard lens Long throw zoom V12H004L06 Middle throw 1 zoom V12H004M04 Middle throw 2 zoom V12H004M05 Rear projectior wide fixed V12H004R03 Replacement remote control 1485872 Advanced projector ceiling mount FI PMRPRG with precision gear Adjustable suspended FI PMRP01 ceiling channel kit False ceiling plate kit FI PMRP02 Structural round ceiling plate ELPMBP03 Adjustable extension column (pipe) 8" - 11" ELPMBC01 Kensington security lock FLPSI 01 50-inch portable screen (4:3 aspect ratio) ELPSC06 60-inch portable pop-up screen (4:3 aspect ratio) ELPSC07 80-inch portable pop-up screen ELPSC08 (4:3 aspect ratio) Duet™ portable projector screen (4:3/16:9 combination) ELPSC80 Component to VGA video cable ELPKC19 S-video cable ELPSV01 Distribution amplifier ELPDA01 Remote control (ELPST16) V12H007T16 Image presentation camera (ELPDC05) V12H162020

Packaging Specifications

PowerLite Pro G5450WUNL

Dimensions 22.4" x 21.6" x 11.1" (W x D x H) Weight 22.1 lb

Genuine Epson Lamp

Dimensions 6.3" x 5.6" x 5.6" (W x D x H)

Weight 0.8 lb Master Carton

Dimensions 28.4" x 13.1" x 6.8" (W x D x H)

Units Per Master Carton 10

Replacement Air Filter Dimensions 11.3" x 3.7" x 1.9" (W x D x H)

Weight 0.21 lb

Master Carton Dimensions 19.2" x 11.8" x 4.8" (W x D x H)

Weight 3.09 lb Units Per Master Carton 10

1 White and color light output will vary depending on mode selected. White light output measured using ISO 21118 standard.

- 2 Data source: ProjectorCentral.com Jan 2010. Average of 910 models for which the manufacturers provided lumens and total power data, all resolutions and brightness levels.
- 4 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency

3 See our website for convenient and reasonable recycling options at www.epson.com/recycle

- 5 This projector does not meet the DICOM standard Part 14 and should not be used as a medical diagnostic device.
- 6 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. 7 Recommended based on normal room conditions. Cleaning requirements may vary depending on use, environment and other conditions. Cleaning intervals may be adjusted to accommodate the environment in which the projector is used.

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

www.epson.com www.epson.ca

Specifications subject to change. Epson, Better Products for a Better Future, Easy Management, Easy MP and Quick Corner are registered trademarks, Epson Exceed Your Vision is a registered logomark and 02Fine is a trademark of Seiko Epson Corporation. PowerLite and PrivateLine are registered trademarks, Duet is a trademark and Epson Connection is a service mark of Epson America, Inc. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2010 Epson America, Inc. CPD-33645 12/10