

TX700

Brilliant Versatile Performer

The Optoma TX700 digital projector is a versatile and portable workhorse. Designed to excel in the most demanding big screen, multimedia environment, the TX700 will shine brightly in a wide range of applications. From the office to school and more, the TX700 is perfect for today and tomorrow's diverse applications.



Features

- **Advanced DarkChip2™ DLP™ technology**
- **Native 1024 x 768 XGA resolution** for sharp display
- **Bright 2200 lumens** for great image quality in a wide range of applications
- **Superior 2500:1 contrast ratio** for cinema quality images and crisp graphics
- **SXGA+ (1400 x 1050) capability** with high-end notebooks
- User **password security** locking system
- Fully **HDTV compatible** (720p, 1080i)
- Convenient **DVI w/HDCP**, VGA/YPbPr, composite, and S-video input
- Weighs only **4.4 pounds**
- **Adjustable cooling fan speed** for high altitude usage



Specifications

Brightness

2200 ANSI lumens

Resolution

Native: 1024 x 768 XGA
Max-Resize: 1400 x 1050 SXGA+

Contrast Ratio

2500:1 (Full On/Full Off)

Lamp Life and Type

2,000/3000(ECO) hour
200W UHP lamp

Display Type

0.55-inch DarkChip2™ DLP™ technology

Weight

4.4 pounds (1.99 kg)

Throw Ratio

1.93 - 2.13:1

Image Size (diagonal)

24.6 to 306 inches
(0.6 to 7.77 meters)

Projection Distance

3.9 to 39.3 feet
(1.2 to 12 meters)

Multimedia Audio

2-watt Mono speaker

Compatibility

XGA, SVGA, VGA, VESA,
Mac, SXGA+ Resized
NTSC/PAL/SECAM
SDTV (480i), EDTV (480p),
HDTV (720p, 1080i)

Horizontal Scan Rate

15 to 100 kHz

Vertical Refresh Rate

56 to 85 Hz

User Controls

Complete onscreen menu
adjustments in 11 languages

I/O Connectors

DVI-D w/HDCP, D-sub15,
VGA for monitor loop through,
S-Video, composite video,
audio minijack

Power Consumption

265 watts (maximum)
<15 watts (standby mode)

Power Supply

AC Input 100 ~ 240V,
auto-switching power supply

Noise Level

28dB

Projection Lens

F= 2.7~3.0, f=21.83~23.81mm,
1:1.2 Manual Zoom and Focus

Dimensions (W x H x D)

9 x 3.7 x 8.26 inches
(230x 95 x 210mm)

Standard Accessories

AC power cord, VGA to VGA,
Composite Video, Remote
control, Batteries for remote,
Lens cap (hanging), Quick start
guide, Warranty card and
Users guide

Optional Accessories

Ceiling Mount, 15-pin to 3 RCA
component/ HDTV adapter,
S-video cable, Audio out adapter,
Universal Remote Mouse kit [USB],
Gold Service warranty, Panoview
projection screen series

Limited Warranty

3 years limited parts and labor,
90 days on lamp

UPC

796435 11 121 2