

PGWX-61B

6,200 lumens, WXGA, single-chip DLP Present projector



WXGA
1280x800

6K
LUMENS

1-CHIP
DLP™

The smart design of the 6,200 lumens Present projector with WXGA resolution will make sure that your meeting's attendees will no longer focus on the projection technology but rather on the content shown on screen.

Why you'll love the Present range

- **Stylish design** that seamlessly blends in with your office interior
- **High-quality images** with an unmatched level of detail and contrast
- **Button-free and cable-free** for simple operation and less clutter
- **Reliable DLP technology** for true ease of mind
- **Easily upgradable** with future connectivity add-ons
- **Low cost of ownership** thanks to DLP technology and sealed optics
- Preset image modes that allow for **flexible color management**
- **Intuitive control menu** with the most common features at your fingertips
- **User-friendly remote control** that features just one button

BARCO

Visibly yours

Technical specifications**PGWX-61B**

Projector type	WXGA single-chip DLP projector
Technology	0.65" DMD
Color wheel	6S standard (RGBYCW)
Resolution	1,280 x 800 WXGA
Brightness	6,200 ANSI lumens / 4,500 ANSI lumens (eco-mode) (measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards)
Contrast ratio	1,100:1 / 4,000:1 (dynamic contrast mode)
Brightness uniformity	85%
Aspect Ratio	16:10
Lens type	G lens
Lenses	1.28-1.60:1; 1.00-1.28:1; 1.61-3.07:1
Optical lens shift	Vertical: -100% to +100% / horizontal: -28% to +28%
Color correction	CCN (for 1 chip)
Lamps	1 x 465W Ushio
Lamp lifetime	Up to 1,500 hours (full power) / Up to 2,000 hours (eco mode)
Transport with lamp	Yes
Sealed DLP™ core	Sealing between TIR prism and DMD
Advance Picture in Picture	Yes
Orientation	table - ceiling
3D	Yes, TI DLP-link
Keystone correction	Yes
Inputs	G/Y, B/Pb, R/Pr, H/C, V; VGA; CVBS; HDMI-1 v1.3 ; DVI-D
Input Resolutions	up to WUXGA (1,920 x 1,200) 60Hz
Software tools	Projector Toolset
Control	IR, RS232, RJ45
Network connection	10/100 base-T, RJ-45 connection
Power requirements	100-240V / 50-60Hz
Max. power consumption	585W @ 110V/540W @ 220V 470W @ 100VAC/460W @ 240VAC (eco mode) / less than 0.5W (standby)
Noise level (typical at 25°C/77°F)	Typical 40 dBA (bright mode) / Typical 37 dBA (eco mode)
Operational ambient temperature	5-40°C / 41°-104°F (sea level)
Operational humidity	10-85%
Dimensions (WxLxH)	475 x 565 x 253.6mm
Weight	17 kg
Shipping dimensions (WxLxH)	934 x 574 x 440 mm
Shipping Weight from Factory	23 kg
Certifications	CB test certificate, US emc, US safety, CE emc and safety, CCC emc and safety
Warranty	3 years standard warranty (warranty and service conditions can differ from region to region. Contact your local sales or service rep for more details)

Generated on: 06 Dec 2013
Technical specifications are subject to change without prior notice.
Please check www.barco.com for the latest information.

BARCO

Visibly yours