

PRODUCT NAME	REALiS WUX4000
ITEM CODE	4964B002
UPC CODE	013803131642



FEATURES

- **Native WUXGA Resolution (1920 x 1200)** - Display true wide screen content in high resolution.
- **LCOS Technology** - High image quality and reliability
- **4th Generation AISYS Optical Engine** - Efficiently handles light, producing superior image quality
- **4000 Lumens** - Bright, crisp images
- **Three Optional Interchangeable Lenses** - Standard, Tele Zoom Lens, and Wide Angle Lens
- **Motorized Lens Shift** - The image can be moved without physically tilting the projector
- **Vivid Photo Mode** - can brightly & vividly express skin tones more naturally
- **Color Correction IC** - 6-axis color adjustment and 3D LUT color reproduction
- **HDMI Deep Color Ver. Input** - Supports full 1080p high definition signal
- **Network Ready RJ-45 Port** - Manage and control multiple projectors from a networked pc
- **Easy-Accessible Lamp, Filter, and Optics Consumption Parts** - The projector's filter can be replaced from the side of the projector, the lamp can be replaced from the rear of the projector and the PS optical filter element of the projector can be replaced from the top of the projector.
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired*

CONTENTS OF KIT

- REALiS WUX4000 Projector
- Lens Cap
- Remote Control (with AAA batteries)
- VGA-VGA Computer Cable
- User Manual

OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION
4966B001	RS-IL01ST STANDARD LENS
4967B001	RS-IL02LZ LONG FOCUS ZOOM LENS
4968B001	RS-IL03WF ULTRA WIDE ANGLE LENS
4965B001	RS-LP06 REPLACEMENT LAMP
4969B001	RS-CL11 CEILING MOUNT
4970B001	RS-RC04 REMOTE CONTROLLER
3096B001	RS-CL08 CEILING EXTENSION: (16" - 24")
3097B001	RS-CL09 CEILING EXTENSION: (24" - 39")
4971B001	RS-FL01 REPLACEMENT FILTER

PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
REALiS WUX4000	00.0 x 00.0 x 00.0 in (000 x 000 x 000 mm)	00.00 lbs (0.00 kg)

* All prices, specifications, and availability subject to change without prior notice.

Canon is a registered trademark of Canon Inc. IMAGEANYWARE is a trademark of Canon.

Effective: March 2011

SPECIFICATIONS

BASIC	IMAGING DEVICE		0.7" LCOS Reflective LCD panels x 3
	ASPECT RATIO		16 : 10
	NATIVE RESOLUTION		1920 x 1200 (WUXGA)
	BRIGHTNESS		4000 Lumens
	UNIFORMITY		88%
	CONTRAST		1000:1
KEYSTONE CORRECTION	VERTICAL	± 20 degrees for Standard / Long Focus Zoom Lens ± 13 degrees for Ultra Wide-Angle Lens	
	HORIZONTAL	-11 to +20 degrees for Standard Lens ± 20 degrees for Long Focus Zoom / Ultra Wide-Angle Lens	
IMAGE ADJUSTMENTS	IMAGE MODE		PC: Standard, Presentation, Vivid Photo, Photo/sRGB, Users(1-5) Video: Standard, Dynamic, Photo/sRGB, Video, Cinema, Users(1-5)
	COLOR PROCESSING		3D-LUT
	MOUNTING		Ceiling, Rear, Rear-Ceiling, Upwards, Downwards
	TILT ANGLE		Adjustable feet up to 6 degrees
INPUT SIGNALS	DIGITAL PC INPUT		WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
	ANALOG PC INPUT		WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
	SCANNING FREQUENCY		H:15 - 75 kHz, V: 50 - 85 kHz
	DOT CLOCK		162 MHz or less
	DIGITAL VIDEO INPUT		1080p / 1080i / 720p / 576p / 480p
	COMPONENT INPUT		1080p / 1080i / 720p / 576p / 480p / 480i
TERMINALS	INPUT	DVI-D 24PIN	Digital RGB Input
		HDMI (Ver. 1.3)	(supports Deep Color) Digital RGB/ Digital Video Input
		MINI D-SUB 15PIN	Analog RGB / Component Video Input / 5BNC
	OUTPUT	MINI-JACK	Stereo x 2
		MINI-JACK	Stereo x 1
	CONTROL	D-sub 9pin	RS-232C
NETWORK		RJ-45	
SPEAKER	5W		
	TYPE		330W NSH (AC)
LAMP	POWER (NORMAL/QUIET)		300 / 264 W
	LAMP LIFE (NORMAL/QUIET)		3500 / 4000 Hours
	REMOTE CONTROL		SENSOR
RATINGS	FAN NOISE (NORMAL/QUIET)		39 / 36dB
	POWER	CONSUMPTION (NORMAL / ECO / STANDBY)	450W / 390W / 0.35W (with LAN off)
		VOLTAGE	AC100 to 240V, 50/60Hz
	TEMPERATURE	OPERATING	41° to 95° F (5° to 35° C)
		STORAGE	-22° to 104° F (-30° to 60° C), 5%RH - 90%RH
	DIMENSIONS (W x D x H)		14.96" x 16.92" x 6.69" without lens
WEIGHT		18.7 lbs without lens	

OPTIONAL LENS SPECIFICATIONS

OPTICS 3 Optional Lenses	RS-IL01ST STANDARD ZOOM LENS	PROJECTION LENS	F1.89 - 2.65 / f= 23.0 - 34.5 mm
		LENS SHIFT	Vertical= 3.5 : 6.5 - 10.5 : 0.5 / Horizontal= 4.6 - 6.4
		ZOOM	1.5x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" x 600"
		PROJECTION DISTANCE	4.26 - 95.14 ft. (1.3 - 29 m) / 100": 10.49 - 15.74 ft. (3.2 - 4.8 m)
	THROW RATIO	1.5:1 - 2.25:1	
	RS-IL02LZ LONG FOCUS ZOOM LENS	PROJECTION LENS	F1.99 - 2.83 / f= 34.0 - 57.7 mm
		LENS SHIFT	Vertical= 3.5 : 6.5 - 10.5 : 0.5 / Horizontal= 4.6 - 6.4
		ZOOM	1.7x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" x 600"
PROJECTION DISTANCE		6.23 - 159.12 ft. (1.9 - 48.5 m) / 100": 15.4 - 26.24 ft. (4.7 - 8.0 m)	
THROW RATIO	2.2:1 - 3.75:1		
RS-IL03WF ULTRA WIDE ANGLE LENS	PROJECTION LENS	F2.0 / f= 12.8 mm	
	LENS SHIFT	Vertical= 4.5 : 5.5 - 5.5 : 4.5 / Horizontal= 4.8 : 5.2 - 5.2 : 4.8	
	ZOOM	1.0x Optical Zoom (Powered)	
	FOCUS	Powered	
	SCREEN SIZE	40" x 600"	
	PROJECTION DISTANCE	2.29 - 17.06 ft. (0.7 - 5.2 m) / 100": 5.67 ft. (1.73 m)	
THROW RATIO	0.8:1		