



XJ-F10X

ADVANCED SERIES

LampFree. MercuryFree. StressFree.

The Casio Advanced Series is the next generation in LampFree. Advanced Series Projectors provide high brightness, up to 3500 ANSI lumens in XGA and WXGA resolutions. Two (2) HDMI inputs provide connectivity with all current display technology without the need for switching cables. A high power USB port (DC 5V,2A) provides direct power for USB stick devices and eliminates the need for a separate power supply. All Casio LampFree Projectors are built to last and backed by an "Industry best" 3 year parts and labor warranty plus 5 years or 10,000 hours on the light source out of the box.

Key Features

- Two (2) HDMI inputs
- Power USB port (DC 5V 2A)
- · Dust resistant design
- Instant Light Control 7 level
- · High Power 16 watt speaker
- 1.5 X Manual Zoom/Focus Lens
- DLP® Technology

LampFree Features

- · Laser & LED Light Source
- Long Life, 20,000 hour estimated operating life
- · No Lamp replacement required
- No Down Time
- Low Power Consumption
- Mercury Free
- Instant On (5 seconds to full brightness)
- Instant Off no cool down required

Terminal Interface



CASIO Projector Specifications	ADVANCED SERIES XJ-F10X
	XGA
Native Resolution	1024 x 768
	4:3
Native Aspect Ratio Brightness	3300 lumens
Display Device	
Contrast Ratio	0.55 -inch DLP® chip 20,000:1
Lens Type	
71	1.5X Manual Zoom & Focus
Lens Offset	3070
Light Source	Laser & LED
Estimated Light Source Life	Up to 20,000 Hours
Screen Size (Min-Max)	30 to 300-inch diagonal
Projection Range	
60-inch screen	6.4 ~ 9.4 ft
100-inch screen	10.9 ~ 15.9 ft
Minimum Throw Distance	3.1 ft
Throw Ratio	1.66-2.42:1
Keystone Correction	Vertical +30° (Auto) Vertical + or - 30° (Manual)
Color Reproduction	Full color (up to 1.07 billion colors)
Power Source	AC100~240V, 50/60Hz
Power Consumption	
Operating	195 W - light control "off" Bright selected
	160 W - light control "on" and "Light Output 7" selected
Standby	0.12 W
TERMINAL CONNECTIVITY	
Video Signal Compatibility	
Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
DTV/HDTV	480i/480p/576i/576p/720p/1080i/1080p
Maximum Computer Input	WUXGA (1920 x 1200) *Reduced blanking signal
INPUTS	
DCR/Component Video Input	mini D-Sub 15 pin x 1 (Also use as YCbCr/YPbPr input— commercially
RGB/Component Video Input	available adapter required)
HDMI	HDMI Type A x 2, HDCP and audio support
Composite Video	Composite Video (RCA) x1, S-Video x1
Audio	RCA (R/L) x1, 3.5mm stereo mini jack x1
USB Power Supply	Yes, DC 5V 2A
USB Input (Host)	No
USB Display	No
Logo Transfer	Micro B(USB1.1) x1
Built-in Memory	No
Wireless Capability	No
OUTPUTS	
Audio	3.5mm Stereo Mini Jack x 1 (variable audio)
AUDIO AND CONTROL SYSTEMS	ADMAN TO T
Audio system	16W Monaural Speaker
Audio system Control Terminal	_
Audio system Control Terminal RS-232	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
Audio system Control Terminal RS-232 LAN	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No
Audio system Control Terminal RS-232 LAN Control System Compatibility	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
Audio system Control Terminal RS-232 LAN	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft)
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7)	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable, Warranty and Safety Precautions
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizex2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable, Warranty and Safety Precautions
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizex2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizex2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No A1-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections	RS-232C (D sub 9 pin) x1, Cross Cable (Null Modem) required No No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizev2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White — 11.8 x 11.8 x 3.8 inches NA
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizex2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White — 11.8 x 11.8 x 3.8 inches
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000–10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White — 11.8 x 11.8 x 3.8 inches NA 8.4lbs —
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information Carton Dimensions	RS-232C (D sub 9 pin) x1, Cross Cable (Null Modem) required No No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizev2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White — 11.8 x 11.8 x 3.8 inches NA 8.4lbs — 15.5 x 13.7 x 6.9 inches
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information Carton Dimensions Carton Dimensions Carton Dimensions Carton Dimensions Carton Dimensions	RS-232C (D sub 9 pin) x1, Cross Cable (Null Modem) required No No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White 11.8 x 11.8 x 3.8 inches NA 8.4 bs 15.5 x 13.7 x 6.9 inches 11.7 lbs
Audio system Control Terminal RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information Carton Dimensions	RS-232C (D sub 9 pin) x1, Cross Cable (Null Modem) required No No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4(not included) Insert Depth 5-8 mm 3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statement included with product for complete details. Wireless Remote Control, Batteries (AAA-sizev2), AC Power Cord, RGB Cable, Warranty and Safety Precautions Soft carrying case YB-2 White — 11.8 x 11.8 x 3.8 inches NA 8.4lbs — 15.5 x 13.7 x 6.9 inches

© 2016 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademarks of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

Designed and Manufactured by Casio in Japan TAA Compliant