

Key **Features**

6,200 Lumen Brightness | Vertical/Horizontal Lens Shift with Centered Lens | Stackable Design | 360degree Installation | SuperColor: Amazing Color Accuracy



Product **Description**

Bright and versatile for any professional installation, the ViewSonic® Pro9510L XGA projector delivers everything you need for big screens in big venues. Delivering 6,200 lumens of advanced high brightness, this projector is ideal for auditoriums, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. Designed for installers, this top-notch performer is also easy to deploy and manage with its wide 1.7x optical zoom adjustment, a centered lens design, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. Thanks to the stackable design of these projectors, light output can be doubled by simply placing one projector on top of the other - perfect for large venues with high ambient light.









call: 888.881.8781Contact Salesemail: salesinfo@viewsonic.comvisit: viewsonic.com

Display: DLP Type: Resolution Type: XGA Resolution: 1024 x 768 Brightness (ANSI Lumens): 6,200 Throw Distance: 3.3 - 55.8 ft / 1 - 17m Throw Ratio: 1.3 - 2.21:1 Display Size (in.): 30 - 300 in. / 0.76 - 7.62 m Keystone: Vertical (± 30°) / Horizontal (± 30°) 1.7x Manual optical zoom / manual Lens: optical focus Light Source (watt): 370 Light Source Life, Normal (hours): 1500 Light Source Life, Dynamic Eco-3500 Mode (hours): Color Depth: 30 bits, 1.07B Color (10+10+10) Aspect Ratio: Vertical (-10.5%/+3%) / Horizontal (+/-Lens Shift: Video Signal: 15-100kHz Frequency Horizontal: Frequency Vertical: 24-120Hz laws. Compatibility: UPC: 766907847918 Up to 1920x1080 PC Resolution (max): **Accessories:** PC Resolution (min): Up to 1920x1080 Connector: USB 2.0 Type A(1), USB 2.0 Type B(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(3), Control (RS232)(1), HDMI 1.4(1), HDMI MHL(1), DVI-D(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), 5-Video In(1), RCA Audio In (L/R)(1), RCA Audio Out(1), 3D VESA(1), Wired Remote In(1), Wired Remote Out(1), 5-BNC(1) Audio: Internal Speakers: 7W (x2) Power: 100~240VAC (Auto Switching), 50-Voltage: 60Hz (universal) Consumption (max): 480W <0.5W Stand-by: **Controls:** Power, H/V lens shift, focus, zoom,

keystone/arrow keys, left/blank,

right/panel key lock, menu/exit,

Display, Image, Video, Audio, Basic,

mode/enter, source

41-104° F (5-40° C)

Advanced

10-85%

Additional Hardware	:
---------------------	---

	Additional Hardware:		
	Kensington Lock Slot:	1	
	Weight (imperial):		
	Net (lbs):	18.26	
	Gross (lbs):	27.31	
	Weight (metric):		
	Net (kg):	8.29	
	Gross (kg):	12.4	
	Dimensions (imperial) (WxHxD):		
	Packaging (in.):	22.68 x 17.17 x 11.46 in.	
	Physical (in.):	17.51 x 12.81 x 5.82 in.	
	Dimensions (metric) (WxHxD):		
	Packaging (mm):	576 x 436 x 291 mm	
	Physical (mm):	445 x 325.5 x 147.8 mm	
	General:		
	Regulations: UL, cUL, FCC, CE, EMC, CB, ROHS, REACH, SVCH, WEEE, ErP, Mexico NOM/ENERGY, PSB, RCM, CCC		
' -	PACKAGE CONTENTS: Pro9510L projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)		
	Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**		
	Recycle/Disposal: Please dispose of in accordance with local, state or federa		

HB10B, PJ-WMK-006, RLC-106, VIEWSTICK2, VIEWSYNC3

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (11/06/2017 08:35 PM PST)

Physical Controls:

On Screen Display:

Temperature:

Operating Conditions:

Humidity (non-condensing):