

# IN5148HD & IN5148HDLC

## High-Performance, Large-Venue Projectors

Part #: IN5148HD, IN5148HDLC

Captivate your auditorium audience with the high-brightness, HD resolution, optional wireless display and installation flexibility of the IN5148HD and IN5148HDLC large-venue projectors.

### Key Features & Technologies

- Crisp 1080p HD resolution for detailed presentations
- 5,000 lumens display bright, clear images in any light
- Large 1.49-3.02 throw ratio for flexibility to install at a variety of distances and adjust image size
- Motorized zoom, focus and horizontal and vertical lens shift
- LightCast technology for wireless display from mobile devices (LC models only)
- HDBaseT Certified for greater interoperability



#### IN5148HD / IN5148HDLC

1080p (1920 x 1080)  
5,000 lumens  
1.49-3.02 throw ratio

### Install It Where You Need It

The IN5148HD and IN5148HDLC projectors fit into roughly 90% of pre-existing large-venue install applications thanks to their very flexible 1.49-3.02 throw ratio and 2:1 zoom ratio. They are sure to deliver an outstanding high-resolution image in the size you need. No more lenses to switch – plus shifting, focusing, and zooming have all been motorized.

### High Brightness HD

Detailed, clear images make presentations better. The IN5148HD and IN5148HDLC projectors do not disappoint with a very bright 5,000 lumens and 1080p high definition resolution. Your presentations will look as good on screen as they do on your computer display, even with the lights on.

### Well Connected

HDBaseT Certification adds even more installation flexibility. With one LAN cable your projector can get HD digital video and audio, 100BaseT Ethernet, USB 2.0, and various control signals from an HDBaseT device.

### LightCast Wireless Device Collaboration

Unlock InFocus' LightCast technology to wirelessly project your Apple, Windows or Chrome device content using its native AirPlay and Miracast software or our free LightCast Sender. LightCast also gives your projector an Internet browser and digital whiteboard to use without connecting a device. LightCast comes unlocked in the LC model.



# Specifications\*

Projector	IN5148HDLC	IN5148HD
Native Resolution	1080p (1920x1080)	
Brightness (Eco/High)	4,000 / 5,000 lumens	
Lamp Life (Eco/Low/Normal)	4,500 hrs / 4,000 hrs / 3,000 hrs	
Lamp Power Eco/Low/Norm	110w / 292w / 365w	
Contrast Ratio	12,000:1	
Color Wheel	6 segment, 2x speed	
Input Sources	HDMI 1.4 x 2, VGA x 2, 1 x Composite Video, S-Video, RJ45, RJ45 HDBaseT, 3.5 mm x 2	
Output Sources	Monitor out (VGA), Audio out (3.5 mm)	
Basic PC Compatibility	VGA (640x480), wVGA (854x480), SVGA (800x600), wSVGA (1024x600), XGA (1024x768), wXGA (1280x800), wXGA+ (1440x900), SXGA (1280x1024), wSXGA+ (1680x1050), UXGA (1600x1200), wUXGA (1920x1200)	
PC-Less Compatibility	LightCast (LightCast, Airplay, Miracast), Compatible with INA-LCKEY only, USB Type A x2 file reader	
Wireless Display	LightCast Key Included	LightCast Ready
Digital Whiteboard**	LightCast Key Included	LightCast Ready
Internet Browser**	LightCast Key Included	LightCast Ready
Control	RS232, Ethernet RJ45 x2, USB 2.0 Type A x2	
3D	Supports 3D content from Blu-ray, cable boxes, dish services and more (over HDMI) at 144Hz. Also supports PC-based content configured at 1080p running at 120Hz. DLP Link 3D glasses required.	
Audible Noise	32 dBA Normal Mode (30 dBA Eco Mode)	
Keystone Correction	± 40° Vertical	
Lens Shift Horizontal	+/-36.8%	
Lens Shift Vertical	+/-85.7%	
Lens Type	Fully Motorized	
Lens - Throw Ratio - Zoom Ratio	1.49 - 3.02 / 2.0:1	
Number of Colors	1.07 billion	
Aspect Ratio	16:9 (Standard) / 16:10-4:3 (Compatible)	
Synch Scan Freq	Horizontal: 15K - 91 kHz / Vertical: 24 - 120 Hz	
Video Compatibility	Standard: NTSC, NTSC 4.43, PAL / M / N, SECAM; SD: 480i, 480p, 576i; HD: 720p, 1080i, 1080p	
Audio	10W - 2x	
Product Dimensions - W x D x H	19.3 x 12.4 x 6.6 in / 490 x 314 x 167 mm	
Product Weight	19.5 lbs / 8.6 kg	
Shipping Dimensions - W x D x H	22 x 9.5 x 18 in / 559 x 241 x 457 mm	
Shipping Weight	23 lbs / 10.4 kg	
Maximum Altitude	10,000 ft / 3,048 m	
Operating Temp.	32 - 104° F / 0 - 40° C	
Security Features	Security lock slot, Security bar, User PIN	
Ships with - Accessories	Power cord, VGA cable, Safety instructions, User manual, Remote control	
Warranty	1 year (product), 6 month (lamp), 90 days (accessories)	
Menu Languages	24 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic, Vietnamese, Indonesian, Persian, Czech, Romanian, Hungarian)	
Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe), CCC+CECP (China), KCC (Korea), IRAM (Argentina), NOM (Mexico), PCT/CU/EAC (Russia), PSB (Singapore), SABS (South Africa), SASO (Saudi Arabia), CB, Nemco/GS, KC	

\* Product specifications, terms, and offerings are subject to change at any time without notice.

\*\* Wireless keyboard and mouse are recommended for digital whiteboard and Internet browser usage

## Accessories

Replacement Lamp (SP-LAMP-096)  
 Universal Ceiling Mount (PRJ-MNT-UNIV)  
 DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)  
 LightCast Key (INA-LCKEY1)  
 Presenter 2 RF Remote (HW-PRESENTER-2)  
 Extended warranties (PROJ-EW1YR-I, PROJ-EW2YR-I)  
 LiteShow 4 (INLITESHOW4)  
 Wireless Keyboard and Mouse (INA-AIRMSKB)



LightCast Key included  
 free with LC Model

