

JVC

DLA-VS4700

Visualization Series™ e-shift 8K D-ILA Projector

BLU^{ESCENT}

Laser-Phosphor Illumination
w/Frame-Encoded Dynamic Laser Control

17.7MP Effective Resolution
120Hz Frame Rate

Any Orientation Operation

Stimulated NVG
Compatible

Digital Smear Reduction
w/Black Frame Insertion

>12,000:1 Contrast Ratio



D-ILA®

● Features

- Laser-Phosphor Illumination System with 20,000+ hour lifetime for Low Operating Cost and Consistent Performance
- 3 Active Matrix, 0.69" Digital D-ILA Devices
- 4096x2160 Native Resolution (8192x4320 addressable 8K e-shift mode)
- 3000 Lumens (typical) - 2400 Lumens (minimum)
- Contrast Ratio - >12,000:1 minimum
- 12-Bit Color Bit Depth via DisplayPort 1.2a Inputs
- 6- Axis Color Management System
- 12-Bit Gamma Correction
- Digital Smear Reduction via Black-frame Insertion
- Low-Latency Signal Processing
- 50Hz, 60Hz, 120Hz Synchronous Operation
- 100%>25% Illumination Control (125 steps), Auto-Intensity Function
- High Contrast IR output for stimulated NVG applications
- User Adjustable Gamma Tracking
- Long-life Wiregrid Polarizers
- Long-life Inorganic Optical Components
- Available Fixed and Zoom Lenses
- Flexible Orientation - Unlimited Pitch and Roll
- 11x11 Matrix, 1/16 pixel Micro-Convergence Control
- Comprehensive LAN/RS232 Control Protocol
- USB Configuration Save/Restore Capability
- Rugged Chassis for Motion-Base Applications

*Shown with optional lens

Specifications

Image Device	3 D-ILA® devices (0.69 inches diagonal), 4096 x 2160, >90% Aperture Ratio
Brightness	3000 ANSI Lumens (typical) - 2400 Lumens (minimum)
Display Resolution	4096 x 2160 Pixels (8192x4320 addressable in e-shift mode)
Contrast Ratio	Greater than 12,000:1 (Sequential)
Uniformity	Greater than 78%
Color Management	6-Axis adjustable CMS
Gamma Control	Std 2.2 Gamma and 3 user adjustable presets
Input - Supported Resolutions	640x480, 800x600, 1280x720, 1024x768, 1366x768, 1280x800, 1440x900, 1280x1024, 1920x1080, 2048x1080, 1600x1200, 1920x1200, 2048x1536, 2560x1600, 3840x2160, 4096x2160
Input modes	50Hz, 60Hz, 120Hz - Single, Dual, Quad Stripe or Quadrant Mode
Latency	30ms@50Hz, 25ms@60Hz, 16.6ms@120Hz
Color Bit Depth	12-bit Input, 12-bit Display
I/O Terminals	DisplayPort 1.2a x 4, LAN, RJ45 x 1, RS-232C, D-Sub 9 pin (male) x 1 Wired Remote (Mini) x 1, USB (for Service), Sync Out
Remote Control	RS-232C/LAN Fully featured control protocol - Wired/IR Remote Control
Projection Lens (optional)	VSL2010 .99:1 - Fixed Lens, ± 50% V, ± 10% H Offset VSL2012 1.18:1 - Fixed Lens, ± 50% V, ± 10% H Offset GLMZ-4009SZ 0.94-1.3:1 - Zoom Lens, ± 50% V, ± 18% H Offset GLMZ-4014SZ 1.27-2.54:1 - Zoom Lens, ± 100% V, ± 40% H Offset
Light source	Blue Laser/Excited Phosphor - 20,000hrs to 50% output at full power User adjustable, 125 steps, 100%-25% Power Level, Auto-Intensity function 8-step Illumination System Aperture Control
Light Source Life	Average 20,000hrs to 50% output at 100% power setting
Power Requirement	AC 100V-240V, 50/60Hz (single phase)
Power Consumption	750 Watts Maximum, 1.5W Standby
Noise Level (0-26°C, 32-79°F)	40dB (A) at 39.4"/1m (3.3ft)
Operating Altitude	<6600ft (2000m) for safe operation
Installation Orientation	Any Orientation is supported - unlimited pitch and roll - motion compliant
Airflow Requirements	106cfm (3m³) per minute minimum
Dimensions (W x H x D)	19.7" x 8.46" x 28.3" (500 x 215 x 720mm)
Weight	77lbs, (35kg) - Lens additional
Supplied Accessories	Power Cord x 2 (US, EU) *Instruction manual is available from the JVC site
Approvals	Safety - CSA C22.2 No.60950-1-07 /UL60950-1 2nd (NA), IEC60950-1:2005/A1:2009/A2:2013, EN60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013 (EU) GB4943, 1-2011 (China) Safety (Laser) - IEC60825-1 Ed2:Class 3R, (US), IEC60825-1 Ed3:Class 1 EMI - FCC PART 15 SUBPART B, CLASS A (US), ICES-003 Issue 5:2012 CLASS A (CAN), EN61000-3-2, EN61000-3-3, EN55032 (Class A), EN55022 (Class A), EN55024 (EU), CISPR22-2009/A1:2010 Class A (AS/NZ) GB9254-2008, GB17625.1-2012 (China) Environmental - RoHS, Proposition 65 (US), WEEE, REACH, New Battery Directive (EU)
Warranty	Two-Years Parts and Labor (per JVC Limited Warranty)

Accessories

VSL2010
0.99:1 Fixed Lens



VSL2012
1.18:1 Fixed Lens



GLMS-4009SZG
0.94-1.3:1 Zoom Lens



GLMZ-4014SZG
1.27-2.54:1 Zoom Lens



DLA-VS4500
Rear View



FLT-VS45
Motorized Filter Holder

JVC

2201 E. Dominguez Street
Long Beach, CA 90810

<http://pro.jvc.com/visualization>

JVCKENWOOD

D-ILA is a trademark of JVCKENWOOD Corporation
E.&O.E., Design and specifications are subject to change without notice.
All brand names and product names are trademarks, registered trademarks,
or trade names of their respective holders.

Copyright 2017, JVCKENWOOD Corporation
All rights reserved