Part #: INV30



The InFocus INV30 projector provides a bright high-resolution image on a short boom delivering high-definition, high-performance interactivity that is virtually shadow-free and glare-free.

The projector supports video and audio connections from a variety of devices including DVD and Blu-ray[™] players, document cameras, and other high-definition sources, and can project media from these sources onto the interactive screen. All HDMI 1.4 inputs are HDCP compliant.

Key Features

- XGA (1024 x 768) resolution
- ♦ 3000 lumens
- ♦ High 17000:1 contrast ratio
- HDMI 1.4 connectivity
- Accurate and vivid color reproduction with BrilliantColor™ technology





Specifications*

rojector	INV30
esolution – Native	XGA (1024 x 768)
lisplay Technology	DLP
ideo Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080p
peakers	Mono 5W x 1
amp Brightness	3,000 lumens
amp Brightness – Eco Mode	2,250 lumens
amp Life	6,500 hours
amp Life – Eco Mode	8,000 hours
amp Power	240W
amp Power – Eco Mode	190W
ontrast Ratio	17,000:1
lumber of Colors	16.7 million
ynch Scan Frequency – Horizontal	15 - 72 KHz
ynch Scan Frequency — Vertical	25 - 75 KHz
spect Ratio	4:3
spect Ratio Compatibility	16:9, 16:10, 5:4 with scaling

Projector	INV30
Keystone Correction	± 40°V
Connectors – Inputs	RS232, HDMI 1.4 (rear), Composite video, VGA x2, RJ-45 (Ethernet), 3.5mm audio input x2, USB mini (for service)
Connectors — Outputs	3.5mm audio output, VGA
Audible Noise	< 38 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 32 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, Documentation
Power Consumption	310.0W max
Power Consumption – Standby Mode	0.5W max
Power Consumption – Eco Mode	240.0W max
Power Standard	AC 100 to 240V, 50/60
Operating Conditions	41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m
Throw and Zoom	
Throw Distance – Minimum	1 m
Throw Distance – Maximum	1 m
Throw Ratio – Short-Throw Lens – Minimum	0.63:1
Zoom Ratio	1.1:1
Shipping	
Product Weight	5.8 lbs / 2.6 kg
Shipping Dimensions	13 x 16.3 x 5.8 in / 330.2 x 412.8 x 146.1 mm
Shipping Weight	7.8 lbs / 3.5 kg

 $^{^{*}}$ Product specifications, terms, and offerings are subject to change at any time without notice.