



Take Advantage of Ultra Short-Throw

The Vivitek D757WT ultra short-throw projector featuring DLP®/BrilliantColor™ technologies, 3300 lumens, 10,000:1 contrast ratio. The D757WT creates a 100-inch image with impressive color reproduction and amazing picture performance from about 17.55" (inch) away, and with Full 3D capabilities the D757WT is the solution for the latest widescreen multimedia needs.

Features

- DLP® and BrilliantColor™ technologies by Texas Instruments for sharp and detailed image quality
- 3300 lumens of brightness with a 10,000:1 contrast ratio
- Native WXGA (1280 x800) resolution display up to WUXGA (1920 x1200)
- Ultra short-throw to limit shadows and light glare
- Energy efficient lamps that last up to 10,000 hours (in Eco mode)
- 3D-ready via DLP® Link™, and Blu-Ray 3D functionality
- Connectivity options include: Two (2) HDMI v1.4, two (2) VGA-in, composite video, S-video
- VGA-Out for display on secondary monitor
- Total 20W (10W x2) audio power with audio-in and audio-out ports for external device connection
- RJ45/RS-232 for integration and system administration
- Network ready and Crestron® RoomView™ approved for network monitoring and management
- Sealed optical engine to minimize the impact of dust
- Top-loading, cover for quick and easy lamp replacement



Specifications			
Display Type	Single 0.65" DMD DLP® Technology by Texas Instruments		
Brightness	3300 Lumens (Typical)		
Native Resolution	WXGA (1280 x 800), 16:10 Format		
Native Aspect Ratio	16:10		
Contrast Ratio	10,000:1 (Full On/Off)		
Lamp Life and Type	5,000/10,000 Hours (Normal/Eco Mode), 230W/200W		
Throw Ratio (±3%)	0.35:1 (Distance/Width)		
Zoom Ratio	Fixed Lens, Manual Focus		
Projection Lens	F=2.5, f=5.1mm		
Image Size (Diagonal)	80" to 100" (203 to 254cm)		
Projection Distance (D) <small>(Distance between projector rear and display surface)</small>	11.11" to 17.55" (283 to 446mm)		
Lens Shift (Based on Full Image Height)	Limited Lens shift Vertical +3.5%		
Offset (Based on Full Image Height)	120%		
Keystone Correction	±40° Vertical, ±40 Steps		
Color Spectrum	1.07 Billion		
Horizontal Scan Rate	15, 30 to 91.4 KHz		
Vertical Scan Rate	24 ~ 30Hz, 47 ~ 120 Hz		
Speaker	10W Mono (x2)		
Remote Control	Fully Featured IR Remote with Laser Pointer		
Projection Method	Table Top or Ceiling Mount (Front or Rear)		
Uniformity	85%		
Computer Compatibility	WUXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible		
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)		
I/O Connection Ports	HDMI v1.4 (x2)	VGA-Out	
	VGA-In (x2)	Audio-Out (Mini-Jack)	
	S-Video	3D-Sync	
	Composite Video	USB A (Power Only)	
	Audio-In	RCA (L/R)	USB B (Service Only)
		Mini-Jack	RJ45 (LAN Control)
	Microphone (Mini-Jack)	RS-232c (Serial Control)	
Security	Kensington® Lock Port, Security Bar		
Weight	11lbs (5.0 kg)		
Dimensions (W x H x D) <small>(Not including height of mirror)</small>	11.3" x 4.9" x 14.7" (287.7 x 126.6 x 374.5 mm)		
Noise Level	33dB/29dB (Normal / Eco. Mode)		
Power	Supply: AC 100-240V, 50/60Hz Consumption: 250W (Eco Mode), 290W (Normal Mode), <0.5W (Standby Mode)		
Operating Temperature	41 to 104°F (5 to 40°C)		
Warranty	5-Year Limited Parts/Labor, 1-Year on Lamp		
Standard Accessories	AC Power Cord, VGA Cable, Interactive Pen (x2), Remote Control, Batteries for Remote, User Manual (CD), Warranty Card, Wall Mount (%WM-3)		
Optional Accessories	Spare Lamp P/N (5811118004-SVV)		
	Remote Control P/N (5041841300)		
UPC	813097023483		